

Vials and caps

SureSTART collection

Streamlined choice. Trusted quality.



thermo scientific



Introduction

Streamlined choice. Trusted quality. SureSTART vials, caps, inserts, well plates, mats and accessories.

Excellence from start to finish

The Thermo Scientific[™] SureSTART[™] sample handling collection includes a range of sample storage and analytical vials and well plates previously sold under Thermo Scientific[™] National[™], Thermo Scientific[™] Chromacol[™] and Thermo Scientific[™] Sun-SRi[™] product names.

All these products have been transitioned and absorbed into one collection so we can deliver a first-class product experience to our customers from the moment you start your purchasing journey, to provide you with performance, instrument compatibility, affordability and delivery that you need.

We understand that not every experiment or analyte is the same, and that you need products that can meet your performance and pricing requirements. You can find three different waves on each our our glass vials, making it easier for analysts to select the right products.

With the SureSTART collection, we ensure that no HPLC/UHPLC or GC system gets left behind. Our vials and well plates are suitable for standard instruments from all vendors, streamlining and simplifying your stockroom—and your budget.



Section contents

Why choose Thermo Scientific SureSTART collection?	6
SureSTART Performance levels	7
Selection guides for vials and well plates	9
Certified integrity and consistency	13
SureSTART Performance level 1 products: Everyday analysis	14
Screw vials and associated caps (2 mL)	15
Crimp vials and associated caps (<2 mL)	19
Snap vials and associated caps (2 mL)	21
Plastic inserts	23
Headspace vials and associated caps (20 mL)	24
Stoppers	26
Specification certified kits	27
Storage	29
SureSTART Performance level 2 products: High throughput analysis	30
Screw vials and associated caps (<2 mL – 2 mL)	32
Crimp vials and associated caps (2 mL)	39
Snap vials and associated caps (2 mL)	42
Screw vials and associated caps (4 mL)	46
Headspace screw vials and associated caps (10 mL vials, 18 mm caps)	48
Headspace crimp vials and associated caps (10 mL – 20 mL vials, 20 mm cap	os) 50
Headspace screw vials and associated caps (20 mL, 18 mm closure)	53
Stoppers and septa	54
EPA vials and caps	55
Stoppers and septa	63
Specification certified vial and cap kits, EPA kits, and scintillation kits	64

Section contents (continued)



	SureSTART Performance level 3 products: High performance	74
	Screw vials and associated caps (<2 mL – 2 mL)	76
	Crimp vials and associated caps (<2 mL – 2 mL)	87
	Snap vials and associated caps (<2 mL – 2 mL)	92
	Inserts	99
	Headspace crimp vials and associated caps (6 mL – 20 mL)	101
	Specification certified, LC/GC certified, MSCERT and MSCERT+ kits	105
	SureSTART vials and caps accessories	119
	Manual crimpers and decrimpers	119
	Electronic crimpers and decrimpers	120
	WebSeal Performance level 1 products: Everyday analysis	124
	Well plates and mats	124
	WebSeal Performance level 2 products: High throughput analysis	128
	Well plates and mats	128
~	WebSeal Performance level 3 products: High performance analysis	132
	Well plates and mats	132
	WebSeal kit accessories	135

Why choose Thermo Scientific SureSTART collection?

Five main benef	ïts to you	More ways to master your testing
	Assured quality and performance	Need standards of quality and performance? Our SureSTART collection has you covered, ensuring you can meet regulatory requirements.
	Instrument compatibility	Our collection contains a broad selection of products to provide complete compatibility for add-on and integrated chromatography autosamplers.
	Sample security and low compound adsorption	Protect your samples from being affected by pH shifting, adducting or contamination, and prevent analyte loss from either the cap top or analyte adsorption to the glass surface.
****	Better product experience	Our SureSTART collection is segmented into three different Performance levels, with visual waves on each glass vial to ensure you always select the right product for your experiment, every time.
	Power to extend your consumables budget	We offer several ways to realize extra value and extend your budget, including built-in bulk discounts—the more you buy, the more you save.



SureSTART Performance levels

Greater choice for what matters most

We are committed to providing a broad selection of solutions for all your chromatography and sample storage requirements.

Our vials and autosampler well plates are consistently manufactured with the lowest levels of extractables and leachables. They are also made from glass that has the lowest compound adsorption, and plastic that is tested and approved for analytical use.

We have high level of standards and certification available in the marketplace so that you can obtain highly reproducible data.

Whether you have routine samples, or you need to ensure high level of confidence and compliance, our market-leading collection of storage and autosampler vials, well plates and sample handling accessories has everything you will need

One collection. Three performance levels. All from one trusted source.

Want to learn more?

ΠП

цШ



Watch this short video to learn how two products can support you with improving your results.

Analytical performance requirements

Products		Detector type	Description
	Thermo Scientific [™] SureSTART [™] Performance level 1 products	Non-MS	Suitable for QA/QC applications using core detectors, <i>e.g.</i> , UV/Vis, PDA, RI, ELSD, FLD, FID, NPD, ECD, TCD, or FPD. Compound concentrations are at easily detectable levels.
	Thermo Scientific [™] SureSTART [™] Performance level 2 products	MS	Suitable for routine QA/QC applications using MS technology. Compound concentrations are at easily detectable or low levels of detection.
	Thermo Scientific [™] SureSTART [™] Performance level 3 products	MS	Suitable for challenging applications, and research-focused applications, using MS technology. Compound concentrations are at/near the method detection limit.



Performance level 1 Everyday analysis: Chromatography approved





Performance level 2 High throughput: Robust and reproducible





Performance level 3 High performance: Selective and sensitive



Selection guide for vials and well plates Which SureSTART product/Performance level is right for you?

There are several factors to consider when choosing a vial or well plate for your application. This section will help guide you through this process to determine which combination is most suitable for your application requirements



thermofisher.com/surestart

Choosing your vials and inserts

The chart below provides a quick guide to selecting the right vial/insert and material for your experimental and application requirements

	Performance			Sample volume	
Non-MS Compound levels not challenging	MS Compound levels at relatively low levels	MS Compound levels near method detection limit or for research analysis	Not sample limited	Volumes vary	Limited
Ļ	Ļ	Ļ	Ļ	Ļ	Ļ
SureSTART Performance level 1 General purpose: chromatography approved	SureSTART Performance level 2 high-throughput: for applications requiring robust and reproducible results High-throughput: for applications requiring robust and reproducible results	SureSTART Performance level 3 High performance: for applications requiring high selectivity and sensitivity	2 mL vial SureSTART Performance level 1, 2 and 3	High recovery vial Total recovery vial SureSTART Performance level 3	Polyspring insert (self-aligning) Pulled insert (economical choice) Fused insert vial 2 mL vial with separate inserts SureSTART Performance level 2 and 3

	Compound polarity		Compoun	d volatility	Compoun	d stability
Non-polar Mid-polar	Polar	Highly polar	Volatile	Non-volatile	Light-stable	Light-sensitive
	Ļ	Ļ	Ļ	Ļ	Ļ	Ļ
Glass vials SureSTART Performance level 1, 2 and 3	*GOLD-grade glass SureSTART Performance level 3	*Silanized glass vials **Polypropylene (PP) vials GOLD-grade glass vials and inserts When low levels of inorganic are required and for solvent stability SureSTART Performance level 1 (PP), 2 and 3 (silanized)	Crimp top vial *Thermo Scientific™ SureStop™ vial Screw thread vial Headspace vials	Screw thread vial Snap-It vial Crimp top vial	Clear vials	Amber vials

*These products can be found in SureSTART Performance level 3

**Not recommended for GC applications

Choosing your septa

The chart below provides a quick guide to selecting the right septa material type for your experimental and application requirements.

Multiple injection?	Temperature?		Thin, fragile needle?	Blunt, thick needle?	Critical analysis?	Low coring?	
Good resealability required	–40 °C to 120 °C	–40 °C to 110 °C	–60 °C to 200 °C	Soft and thin septa required	Pre-slit/pre-cut liner as penetration aid (HPLC)	Very clean liner required/ low-extractables	Double-sided PTFE laminated liners required
Ļ	Ļ	Ļ	↓	Ļ	Ļ	Ļ	Ļ
Silicone/PTFE Natural rubber/ TEF	Natural rubber/ TEF Butyl/PTFE	RedRubber/ PTFE	Silicone/PTFE	Silicone/PTFE	Silicone/PTFE, pre-slit septa	Silicone/PTFE	PTFE/silicone/ PTFE

Choosing your well plates and mats

Selecting the perfect Thermo Scientific[™] WebSeal[™] well plates and mats for your chromatography requirements is easy using our selector tools and resources.

Performance requirements			Compour	Compound polarity		arity Sample availability	
Compound levels not challenging	Compound levels not challenging/ relatively low levels	Compound levels at/near method detection limit	Water and polar	Hydrophobic (e.g., proteins and peptides)	Unlimited	Limited	Very limited
Ļ	Ļ	Ļ	Ļ	Ļ	Ļ	Ļ	↓
WebSeal Plastic, chromatography tested	WebSeal certified products Plastic, MS tested	WebSeal Plate+ Glass-coated plates Plate with glass inserts	WebSeal plastic and certified	WebSeal Plate+ Glass-coated plates Plate with glass inserts	Flat bottom Where sample volume is high	U-Bottom Where sample volume is low	V-Bottom Where sample volume is very low

Microtitre: 14-16 mm (also referred to as microwell and standard well plate) Mid well plate: 20-41 mm Deep well plate: >44 mm

Autosampler compatibility							
Agilent	CTC (PAL)	Thermo Scientific™ TriPlus™ RSH*	Shimadzu	Thermo Scientific [™] Vanquish [™] **	Waters ACQUITY		
↓	Ļ	Ļ	Ļ	Ļ	Ļ		
	Mid well plate						

*TriPlus RSH with 6-drawer stack can accommodate 24 microtitre 15.5 mm plates microtitre well plate **Barcoded plates for complete orientation



Examples of microtitre, mid well and deep well plates shown above

Certified integrity and consistency



With over 40 years of experience supplying vial and well plates, Thermo Scientific SureSTART certified products are supplied to meet 'critical to quality' specifications, consistently. SureSTART products are produced in compliance with ISO 9001 requirements.

In addition, SureSTART certified products include:

- Glass vials made from First Hydrolytic Type 1 A borosilicate glass, which conforms to U.S Food and Drug Administration (FDA), USP and EU Pharmacopeia standards
- Chemically and thermally resistant well plates are made of high quality materials
- Our autosampler WebSeal wellplates all conform to ANSI SLAS 4-2004 standards
- In-line opto-electronic testing inspects 100% of all key dimensions

- Our well plates are chromatography tested for solvent compatibility and inertness to ensure your data quality is not compromised
- Packaged in material that has been tested and selected for cleanliness
- Subjected to rigorous end-of-line sampling and quality control procedures to ensure all vials remain within specification
- Most glass vials come with a non-removable write-on patch convenience and ease-of-use
- Patented products, such as Advanced Vial Closure System (Thermo Scientific[™] AVCS[™]) caps designed to minimize sample evaporation
- Products produced and/or packed in a clean environment to reduce contamination
- Glass vials which are available deactivated/silanized

AVCS caps and SureStop vials

The next-generation of sample handling

The patented Thermo Scientific[™] SureStop[™] and AVCS technology is designed to remove subjectivity around achieving the optimal closure compression when closing a vial. As an integral component of AVCS technology, SureStop vials offer the sealing and performance characteristics of a crimp top vial and the versatility and convenience of a screw thread vial. This is achieved by incorporating a definite stop point into the design of the vial finish, preventing over tightening of the closure.

Compatible with all LC and GC autosamplers, our SureStop vials with our AVCS caps:

- Effectively closures every time
- Obtain cleaner spectra
- More consistent data for GC and LC applications
- Reduce instrument downtime and ensure sample throughput
- Standardize your stockroom



Examples of vial and closure misalignment/deformation.

- (A) SureStop vial self aligning cap;
- (B) generic vial, cap tilt;
- (C) generic vial, septum dislodged;
- (D) generic vial, deformed top.



Cap tilt and septum displacement due to over tightening

SureStop provides optimal cap positioning

Performance level 1: Everyday analysis



Chromatography approved Meet your chromatographic needs

Choose the right vial for chromatographic analyses. Thermo Scientific SureSTART Performance level 1 products are designed for everyday chromatography analysis. They provide an affordable choice for use with all GC and HPLC/UHPLC instrument types.

If you are verifying compound presence and quantification using detection techniques such as UV/Vis, PDA, RI, ELSD, FLD, FID, NPD, ECD, TCD, or FPD, our Performance level 1 products are the perfect solution for you–select the products with the one wave.

Within Performance level 1 you will find a selection of vials (glass, plastic, <2 mL, 2 mL and headspace) and specification certified convenience kits.

You can also find a great selection of standard and bonded caps to support robotic autosamplers within this Performance level.

Need stoppers? These can also be found within this Performance level.

Vials	Caps
<2 mL PP screw microvials	— 0 mm corow copo
2 mL glass screw vials	 9 mm screw caps
2 mL glass crimp vials	11 mm crimp caps
<2 mL PP snap microvials	11 mm snap caps
Plastic inserts	_
20 mL glass crimp headspace vials	20 mm crimp caps
20 mm stopper	_
Specification certified kits	_
Storage	_

Performance level 1

for everyday analyses

- Packaged in material that has been tested and selected for cleanliness
- All products within this performance level are suitable for use with GC and HPLC/UHPLC
- Headspace vials and caps available in 20 mL options
- Vials are identified by one wave and a convenient write-on patch as standard
- Vials and caps available as screw, snap and crimp
- Vials available as clear or amber glass and as either glass or plastic
- Vial volume sizes ranging from 0.3 mL to 20 mL covering limited sample volumes to headspace analyses
- Caps come in a choice of PP, aluminum and magnetic steel caps with silicone/PTFE, rubber/TEF, or butyl/PTFE septa
- Use Thermo Scientific[™] manual or electronic crimpers and decrimpers for easy application and removal of crimp caps
- Buy vials and caps in bulk for greater savings

Specification certified

- All SureSTART vials are dimensionally verified to ensure autosampler compatibility
- Automated optical and gauge inspection to ensure critical dimensions and tolerances
- Vials meet all relevant requirements of US, EU, JPN Pharmacopia
- Uniform and defect-free

Lot traceable

- 100% traceable through the manufacturing process
- Certificate of conformance (CoC) available by lot number upon request



<2 mL polypropylene screw microvials

Performance level 1 for everyday analysis

Description

- Short thread screw
- 12 mm × 32 mm (diameter × height)
- No marking spot
- Specification certified

For use with 9 mm screw caps, or 9 mm AVCS screw caps







Key attributes	Suitable for PFAS analysis	Suitable for PFAS analysis
Vial color and material	Clear plastic	Clear plastic
Total volume	0.4 mL	1.5 mL
Usable volume	0.3 mL	1 mL
Residual volume	4 µL	170 µL
Ordering information	Cat. no.	Cat. no.
100/pack	6ESV9-04PP	6ESV9-1PP
10 x 100/pack	6ESV9-04PPT	6ESV9-1PPT
50 x 100/pack	6ESV9-04PPF	6ESV9-1PPF



2 mL glass screw vials

Performance level 1 for everyday analysis

Description

- Short thread screw
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- Specification certified

For use with 9 mm screw caps, or 9 mm AVCS screw caps





9 mm screw caps

Performance level 1 for everyday analysis

Description

- Short thread screw
- 9 mm
- Specification certified

For use with <2 mL and 2 mL screw vials

Key attributes	-	_	_	Pre-slit septa	Suitable for PFAS analysis
Cap color and material	Blue PP	Blue PP	Blue PP	Blue PP	Clear PP
Septum color and material	Red natural rubber/ clear TEF	Red silicone/ivory PTFE	White silicone/red PTFE	White silicone/blue PTFE	Integral PP septum, thinned penetration area
Septum thickness	1 mm	1 mm	1 mm	1 mm	_
Septum hardness	60° shore	45° shore	55° shore	55° shore	-
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack 🗳	CHSC9-10	<u>CHSC9-20</u>	<u>CHSC9-30</u>	<u>CHSC9-40</u>	6ESC9-50
10 x 100/pack	<u>CHSC9-10T</u>	CHSC9-20T	CHSC9-30T	CHSC9-40T	_
50 x 100/pack	CHSC9-10F	CHSC9-20F	CHSC9-30F	CHSC9-40F	-



9 mm screw caps (continued) Performance level 1 for everyday analysis

Description

- Short thread screw
- 9 mm
- Specification certified

For use with <2 mL and 2 mL screw vials

	Bonded	Bonded	Bonded	Bonded
Cap color and material	_	Pre-slit septa	_	Pre-slit septa
	Blue PP	Blue PP	Blue PP	Blue PP
Septum color and material	White silicone/ red PTFE	White silicone/ red PTFE	White silicone/ white PTFE	White silicone/ white PTFE
Septum thickness	1 mm	1 mm	1 mm	1 mm
Septum hardness	45° shore	45° shore	45° shore	45° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	CHSC9-30UB	CHSC9-30UBS	CHSC9-35UB	CHSC9-35UBS
10 x 100/pack	_	_	CHSC9-35UBT	CHSC9-35UBST
50 x 100/pack	_	—	CHSC9-35UBF	CHSC9-35UBST

Crimp vials and associated caps (2 mL, 11 mm caps)

Seal these crimp vials with 11 mm aluminum

crimp caps and septa using a manual or electronic crimper tool.

2 mL glass crimp vials

Performance level 1 for everyday analysis

Description

- Crimp closure (11 mm)
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- Specification certified

For use with 11 mm crimp caps





11 mm crimp caps

Performance level 1 for everyday analysis

Description

- Crimp closure (11 mm)
- Specification certified

For use with <2 mL and 2 mL crimp vials, or <2 mL and 2 mL snap vials Use with 11 mm crimpers and decrimpers

Cap color and material	Silver aluminum	Silver aluminum	
Septum color and material	Natural rubber/clear TEF	White silicone/red PTFE	
Septum thickness	1 mm	1.3 mm	
Septum hardness	60° shore	45° shore	
Ordering information	Cat. no.	Cat. no.	
100/pack	<u>CHCC11-10</u>	<u>CHCC11-30</u>	
10 x 100/pack	<u>CHCC11-10T</u>	<u>CHCC11-30T</u>	
50 x 100/pack	CHCC11-10F	CHCC11-30F	

Learn more about:

Manual and electronic crimpers and decrimpers



Snap vials and associated caps (<2 mL vials, 11 mm caps)

<2 mL polypropylene snap microvials

Performance level 1 for everyday analysis

Description

- Snap (11 mm)
- 12 mm × 32 mm (diameter × height)
- No marking spot
- Specification certified
- These vials can be used for PFAS analysis

For use with 11 mm snap caps

Key attributes	Suitable for PFAS analysis	Suitable for PFAS analysis	Suitable for PFAS analysis
Vial color and material	Clear PP, conical	Clear PP, conical	Clear PP, flat bottom
Total volume	0.3 mL	0.8 mL	1.0 mL
Usable volume	0.2 mL	0.6 mL	0.8 mL
Residual volume	4 μL	6 µL	80 µL
Ordering information	Cat. no.	Cat. no.	Cat. no.
100/pack	6ERV11-03PPC	6ERV11-08PPC	6ERV11-08PPFB
10 x 100/pack	6ERV11-03PPCT	6ERV11-08PPCT	6ERV11-08PPFBT
50 x 100/pack	6ERV11-03PPCF	6ERV11-08PPCF	6ERV11-08PPFBF



11 mm snap caps

Performance level 1 for everyday analysis

Description

- Snap closure (11 mm)
- Specification certified
- Does not re-seal after puncture
- These caps can be used for PFAS analysis

For use with <2 mL and 2 mL snap vials

	8	
Key attributes	Suitable for PFAS analysis	Suitable for PFAS analysis
Cap color and material	Blue PE snap cap with integral PE membrane	Clear PE snap cap with integral PE membrane
Membrane thickness	0.5 mm	0.5 mm
Septum color and material Septum thickness Septum hardness	This cap comes with no septa	This cap comes with no septa
Ordering information	Cat. no.	Cat. no.
100/pack 🗳	6ERC11PE	6ERC11PEC

Need more

information about which insert is most suitable for you?

Watch this

short video



Plastic inserts for 2 mL vials

Performance level 1 for everyday analysis

Description

- 6 mm × 31 mm (diameter × height) (size × height) conical with polyspring base
- No marking spot but filling lines
- Specification certified
- This insert can be used for PFAS analysis

For use with 2 mL screw vials, 2 mL snap vials or 2 mL crimp vials

Key attributes	Suitable for PFAS analysis	
Insert color and material	Clear PP with clear PP polyspring	
Total volume	0.30 mL	
Usable volume	0.25 mL	
Residual volume	4 µL	
Ordering information	Cat. no.	
100/pack	6EME03CPPSP	
10 x 100/pack	6EME03CPPSPT	
50 x 100/pack	6EME03CPPSPF	

Learn more about:



2 mL glass

screw vials



2 mL glass crimp vials 2 mL glass snap vials





20 mL glass crimp headspace vials

Performance level 1 for everyday analysis

Description

- Crimp
- 22.5 mm × 75.5 mm (diameter × height) square rim
- Marking spot
- Specification certified

For use with 20 mm crimp caps

Vial color and material	Clear glass, round bottom base	Clear glass, flat bottom base
Total volume	20 mL	20 mL
Usable volume	18 mL	20 mL
Residual volume	0.8 mL	0.8 mL
Ordering information	Cat. no.	Cat. no.
100/pack	<u>CHCV20-14</u>	<u>CHCV20-16</u>
10 x 100/pack	<u>CHCV20-14T</u>	_



Headspace vials and associated caps (continued) (20 mL vials, 20 mm caps)

20 mm crimp caps

Performance level 1 for everyday analysis

Description

- Crimp closure (20 mm) .
- Specification certified

For use with 10 mL and 20 mL crimp headspace vials (with diameter neck size of 20 mm) Use with 20 mm crimpers and decrimpers















Cap color and material	Silver aluminum	Silver aluminum	Silver aluminum	Gold magnetic steel	Gold magnetic steel
Septum color and	Molded	_	_	Molded	_
material	Grey butyl/ grey PTFE	Blue silicone/ white PTFE	_	Grey butyl/ grey PTFE	Blue transparent silicone/clear PTFE
Septum thickness	3 mm	3 mm	-	3 mm	3 mm
Septum hardness	50° shore	45° shore	_	50° shore	45° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack 🗳	CHCC20-1	CHCC20-2	-	<u>CHCC20-1M</u>	<u>CHCC20-2M</u>
10 x 100/pack	<u>CHCC20-1T</u>	<u>CHCC20-2T</u>	6ECC20OT	CHCC20-1MT	CHCC20-2MT
50 x 100/pack	CHCC20-1F	CHCC20-2F	-	-	-

Manual and electronic crimpers and decrimpers





20 mm stopper

Performance level 1 for everyday analysis

Description

• Specification certified

For use with vials (e.g. 10 mL/20 mL crimp vials) with diameter neck size of 20 mm



Product description	Stopper (20 mm)
Color and material	Grey bromobutyl
Septum thickness	3 mm
Septum hardness	45° shore
Ordering information	Cat. no.
100/pack	CHBS-20
10 x 100/pack	CHBS-20T
50 x 100/pack	CHBS-20F

Specification certified shell, screw vial and cap kits

Performance level 1 for everyday analysis

Description

- Screw
- 9 mm short thread
- Specification certified











Vial color and material	Clear propylene	Clear propylene	Clear glass shell vial	Amber glass shell vial
Vial total volume	0.4 mL	0.4 mL	1.25 mL	1.25 mL
Cap color and material	Blue PP screw cap	Blue PP screw cap	Lamela PE plug	Lamela PE plug
Septum color and material	White silicone/blue PTFE, pre-slit septa	White silicone/red PTFE	_	_
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	<u>6EKPP97</u>	<u>6EKPP87</u>	—	—
200/pack	_	—	6EKSHV8-1	6EKSHV8-2
Kit vial	<u>6ESV9-04PP</u>	6ESV9-04PP	_	_
Kit closure	<u>CHSC9-40</u>	<u>CHSC9-30</u>	_	_



Specification certified shell, screw vial and cap kits (continued)

Performance level 1 for everyday analysis

Description

- Screw
- 9 mm short thread
- Specification certified
- These kits are suitable for PFAS analysis





Key attributes	Suitable for PFAS analysis	Suitable for PFAS analysis
Vial color and material	Clear PP	Clear PP
Vial total volume	0.4 mL	1.5 mL
Cap color and material	Blue polyethylene snap cap	Clear PP screw cap
Septum color and material	Integral PE septum	Integral PP septum
Ordering information	Cat. no.	Cat. no.
100/pack	6EKRV11PP-08	6EKSV9PP-15
200/pack	_	_
Kit vial	6ERV1108PPFB	6ESV9-1PP
Kit closure	6ERC11PE	<u>6ESC9-50</u>



Vial rack

Performance level 1 for everyday analysis

Description

- For 12 × 32 mm vials
- 50 cavities (5 x 10)
- No lid, reusable 20 x 10.5 x 2.2 cm

Use with 2 mm vials



Product description	Vial rack
Color and material	Blue PP
Ordering information	Cat. no.
1/pack	6EVR1232B

Performance level 2: High-throughput analysis

When robustness and reproducibility are key

Be compliant-ready for your high-throughput samples in regulated environments

Choose Thermo Scientific SureSTART Performance level 2 products to ensure high quality data with an uninterrupted workflow in high throughput applications using GC, HPLC/ UHPLC, single or triple quadrupole MS systems. Use these Performance level 2 vials for routine QA/QC applications, where the analyte levels are achievable or close to the method detection level. These products have very low metal content and extractables and leachables and conform to high standards so that you can meet your regulatory requirements. They are specification certified to ensure their physical dimensions and autosampler compatibility.

If you need products that support routine analyses, our Performance level 2 products are here for you. Select the products with the two waves.

Within Performance level 2 you will find a selection of kits (including our range of U.S. Environmental Protection Agency (EPA) and Scintillation), vials, caps, inserts, septa and stoppers.



Performance level 2

for high-throughput applications

- All products within this Performance level are suitable for GC, HPLC/UHPLC, and mass spectrometry (MS) applications
- Volume sizes ranging from 0.3 mL to 20 mL covering limited sample volumes to headspace analyses
- Headspace vials and caps available from 10 mL 20 mL
- Vials are identified by two waves and a convenient write-on patch as standard
- Vials available as screw, snap and crimp
- Vials available in glass, silanized glass and plastic
- Vials available as clear or amber glass
- Caps available as screw, screw AVCS, snap and crimp
- Use Thermo Scientific manual or electronic crimpers and decrimpers for easy application and removal of crimp caps
- EPA, scintillation and specification certified kits can be found within Performance level 2
- Buy vials and caps in bulk for greater savings

Specification certified

- All Thermo Scientific SureSTART vials are dimensionally verified to ensure autosampler compatibility
- Inspected by automated optical and gauge inspection to
 ensure critical dimensions and tolerances
- Vials meet all requirements of US, EU, JPN Pharmacopia
- Uniform and defect-free

Lot traceable

- 100% traceable through the manufacturing process
- Certificate of Conformance available by lot number upon request

Performance level 2: High-throughput analysis

Vials	Caps	
0.7 mL glass crimp vials	8 mm crimp caps	
1.7 mL high-recovery glass screw vials		
2 mL glass screw vials	9 mm screw caps	
2 mL glass crimp vials	11 mm crimp caps	_
2 mL glass snap vials	11 mm snap caps 11 mm crimp caps	
Inserts for 2 mL vials	_	
4 mL glass screw vials	13 mm screw caps	
8 mL glass screw vials	15 mm screw caps	
10 mL glass screw headspace vials	18 mm screw caps	
10 mL glass crimp headspace vials	20 mm crimp caps	
12 mL glass screw vials	15 mm screw caps	
20 mL glass screw vials	18 mm screw caps	
20 mL glass crimp headspace vials	00	
20 mm stoppers and septa	20 mm crimp caps	
40 mL glass screw vials	24 mm screw caps	_
Kits		l i
Specification certified		
EPA		



0.7 mL glass crimp microvials for <2 mL samples

Performance level 2 for high-throughput applications

Description • Crimp • Conical base • Specification certified For use with 8 mm crimp caps

Vial color and material	Amber glass
Total volume	0.7 mL
Usable volume	0.6 mL
Residual volume	2 µL
Ordering information	Cat. no.
100/pack	<u>6ACV8-07C2</u>

Screw vials and associated caps (continued) (<2 mL – 2 mL vials, 9 mm caps)

1.7 mL high-recovery glass screw microvials for <2 mL samples

Performance level 2 for high-throughput applications

Description

- Short thread screw
- 12 mm × 32 mm (diameter × height) inner V-bottom base
- Marking spot
- Specification certified

For use with 9 mm screw caps, or 9 mm AVCS screw caps

Vial color and material	Clear glass			
Total volume	1.7 mL			
Usable volume	1.3 mL			
Residual volume	4 µL			
Ordering information	Cat. no.			
100/pack	<u>6ASV9-V1</u>			
10 x 100/pack	<u>6ASV9-V1T</u>			



2 mL glass screw vials

Performance level 2 for high-throughput applications

Description

- Short thread screw
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- Specification certified

For use with 9 mm screw caps, or 9 mm AVCS screw caps

Vial color and material	Clear glass	Amber glass	Amber glass, silanized
Total volume	2.0 mL	2.0 mL	2.0 mL
Usable volume	1.5 mL	1.5 mL	1.5 mL
Residual volume	170 µL	170 µL	170 μL
Ordering information	Cat. no.	Cat. no.	Cat. no.
100/pack	<u>6ASV9-1P</u>	<u>6ASV9-2P</u>	<u>6ASV9-S2P</u>
10 x 100/pack	6ASV9-1PT	<u>6ASV9-2PT</u>	_
50 x 100/pack	6ASV9-1PF	6ASV9-2PF	_

Need a smaller volume?

Try our Polyspring glass inserts for small volume samples





9 mm AVCS screw caps

Performance level 2 for high-throughput applications

Description

- Short thread screw
- 9 mm
- Specification certified
- AVCS screw top technology

For use with <2 mL and 2 mL screw vials

Key attributes	Suitable for PFAS analysis	Bonded	Bonded	Close top cap
Cap components	_	Pre-slit septa	_	_
Cap color and material	Blue PP	Blue PP	Blue PP	Blue PP
Septum color and material	White silicone/ beige polyimide	White silicone/ beige PTFE	White silicone/ beige PTFE	Silicone RedRubber™/ ivory PTFE
Septum thickness	1 mm	1 mm	1 mm	1 mm
Septum hardness	45° shore	45° shore	45° shore	45° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack 💕	6ASC9SPI1	6ASC9STBS1	6ASC9STB1	6ASC9CTRRT1
10 x 100/pack	_	6ASC9STBS1T	6ASC9STB1T	_
50 x 100/pack	_	6ASC9STBS1F	6ASC9STB1F	_



9 mm AVCS screw caps (continued)

Performance level 2 for high-throughput applications

Description

- Short thread screw
- 9 mm
- Specification certified
- AVCS screw top technology

For use with <2 mL and 2 mL screw vials


Screw vials and associated caps (continued) (<2 mL – 2 mL vials, 9 mm caps)

9 mm AVCS screw caps (continued)

Performance level 2 for high-throughput applications

Description

- Short thread screw
- 9 mm
- Specification certified
- AVCS screw top technology

For use with <2 mL and 2 mL screw vials

Cap color and material	Green PP	Green PP	Yellow PP	Yellow PP
Septum color and material	White silicone/red PTFE	RedRubber/ivory PTFE	White silicone/red PTFE	RedRubber/ivory PTFE
Septum thickness	1 mm	1 mm	1 mm	1 mm
Septum hardness	45° shore	45° shore	45° shore	45° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	6ASC9ST1G	6ASC9RT1G	6ASC9ST1Y	6ASC9RT1Y



9 mm AVCS screw caps (continued)

Performance level 2 for high-throughput applications

Description

- Short thread screw
- 9 mm
- Specification certifiedAVCS screw top technology

For use with <2 mL and 2 mL screw vials

Cap color and material	Black PP	Black PP
Septum color and material	White silicone/red PTFE	RedRubber/ivory PTFE
Septum thickness	1 mm	1 mm
Septum hardness	45° shore	45° shore
Ordering information	Cat. no.	Cat. no.
100/pack	<u>6ASC9ST1B</u>	6ASC9RT1B

Crimp vials and associated caps (2 mL vials, 11 mm caps)

2 mL glass crimp vials

Performance level 2 for high-throughput applications

Description

- Crimp
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- Specification certified

For use with 11 mm crimp caps





11 mm crimp caps

Performance level 2 for high-throughput applications

Description

- Crimp closure (11 mm)
- Specification certified

For use with <2 mL – 2 mL crimp vials, or <2 mL – 2 mL snap vials Use with 11 mm crimpers and decrimpers

Cap color and material	Silver aluminum closure	Silver aluminum closure	Silver aluminum closure
Septum color and material	White silicone/red PTFE	RedRubber™/clear PTFE	Natural RedRubber/PTFE
Septum thickness	1 mm	1 mm	1 mm
Septum hardness	45° shore	60° shore	60° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.
100/pack 🗳	6ACC11ST1	6ACC11RT1	6ACC11NR1
10 x 100/pack	6ACC11ST1T	6ACC11RT1T	_
50 x 100/pack	6ACC11ST1F	6ACC11RT1F	_

Crimp vials and associated caps (continued) (2 mL vials, 11 mm caps)

11 mm crimp caps (continued)

Performance level 2 for high-throughput applications

Description

- Crimp closure (11 mm)
- Specification certified

For use with <2 mL – 2 mL crimp vials, or <2 mL – 2 mL snap vials Use with 11 mm crimpers and decrimpers

Cap color and material	Silver aluminum closure	Silver aluminum closure	Silver aluminum closure	Silver aluminum closure
Septum color and material	Natural RedRubber/PTFE	Natural RedRubber/PTFE	Natural RedRubber/PTFE	Natural RedRubber/PTFE
Septum thickness	1 mm	1 mm	1 mm	1 mm
Septum hardness	60° shore	60° shore	60° shore	60° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.	
100/pack	6ACC11NR1G	6ACC11NR1R	6ACC11NR1B	6ACC11NR1Y

Learn more about:

Manual and electronic crimpers and decrimpers





2 mL glass snap vials

Performance level 2 for high-throughput applications

Description

- Snap
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- Specification certified

For use with 11 mm snap caps or 11 mm crimp caps



Need a smaller volume?

Try our Polyspring glass inserts for small volume samples



Snap vials and associated caps (continued) (2 mL vials, 11 mm caps)

11 mm snap caps

Performance level 2 for high-throughput applications

Description

- Snap closure (11 mm) •
- Specification certified

For use with 11 mm glass or plastic snap vials

Key attributes	_	_	_	Suitable for PFAS analysis
Cap color and material	Blue PE	Blue PE	Blue PE	Blue PE
Septum color and material	White silicone/red PTFE	Natural rubber/clear TEF	Red silicone rubber/ clear PTFE	White silicone/ red polyimide
Septum thickness	1 mm	1 mm	1 mm	1 mm
Septum hardness	45° shore	60° shore	60° shore	45° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	6ARC11ST1	6ARC11NRT1	6ARC11RRT1	6ARC11SPI1
10 x 100/pack	6ARC11ST1T	6ARC11NRT1T	_	_
50 x 100/pack	6ARC11ST1F	6ARC11NRT1F	_	_





11 mm snap caps (continued)

Performance level 2 for high-throughput applications

Description

- Snap closure (11 mm)
- Specification certified

For use with 11 mm glass or plastic snap vials

	8		8
Cap color and material	Red PE	Red PE	Orange PE
Septum color and material	White silicone/red PTFE	Natural rubber/clear TEF	White silicone/red PTFE
Septum thickness	1 mm	1 mm	1 mm
Septum hardness	55° shore	60° shore	60° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.
100/pack	6ARC11ST1R	6ARC11NRT1R	6ARC11ST10R
10 x 100/pack	6ARC11ST1RT	6ARC11NRT1RT	6ARC11ST1ORT
50 x 100/pack	6ARC11ST1RF	_	_

Snap vials and associated caps (continued) (2 mL vials, 11 mm caps)

11 mm snap caps (continued)

Performance level 2 for high-throughput applications

Description

- Snap closure (11 mm)
- Specification certified

For use with 11 mm glass or plastic snap vials

				8
Cap color and material	Clear PE	Clear PE	Clear PE	Black PE
Septum color and material	Red silicone rubber/ clear PTFE	White silicone/red PTFE	White virgin PTFE	White silicone/red PTFE
Septum thickness	1 mm	1 mm	1 mm	1 mm
Septum hardness	45° shore	60° shore	53° shore	55° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	6ARC11RRT1C	6ARC11ST1C	<u>6ARC11-P</u>	6ARC11ST1B



4 mL glass screw vials

Performance level 2 for high-throughput applications

Description

- Screw
- 15 × 45 mm (diameter × height) flat base
- Specification certified

For use with 13 mm screw caps (13-425)

Vial color and material	Clear glass	Amber glass
Total volume	4.0 mL	4.0 mL
Usable volume	3.5 mL	3.5 mL
Residual volume	800 µL	800 µL
Ordering information	Cat. no.	Cat. no.
100/pack	<u>6ASV13-1P</u>	<u>6ASV13-2P</u>



Screw vials and associated caps (continued) (4 mL vials, 13 mm caps)

13 mm screw caps

Performance level 2 for high-throughput applications

Description

- Screw thread closure (13 mm/13-425)
- Specification certified

For use with 4 mL screw vials (and other vials with screw 13 mm dimensions)

Cap color and material	_	Pre-slit septa	Closed top
Cap color and material	Black PP	White PP	White polyurethane
Septum color and material	White silicone/red PTFE	White silicone/blue PTFE	White UR 13-425 PE foam/PTFE
Septum thickness	1.5 mm	1.5 mm	1.5 mm
Septum hardness	55° shore	45° shore	75° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.
100/pack	6ASC13ST15	6PSC13STS15W	6ASC13-CTP



10 mL glass screw headspace vials

Performance level 2 for high-throughput applications

Description

- Screw
- 22.5 mm × 46 mm (diameter × height) round bottom base
- Marking spot
- Specification certified

For use with 18 mm screw caps

Vial color and material	Clear glass	Amber glass
Total volume	10 mL	10 mL
Usable volume	8 mL	8 mL
Residual volume	0.8 mL	0.8 mL
Ordering information	Cat. no.	Cat. no.
100/pack	<u>6ASV10-1</u>	<u>6ASV10-2</u>
10 x 100/pack	<u>6ASV10-1T</u>	<u>6ASV10-2T</u>
50 x 100/pack	<u>6ASV10-1F</u>	_

Headspace screw vials and associated caps (continued) (20 mL vials, 18 mm caps)

20 mL glass screw headspace vials

Performance level 2 for high-throughput applications

Description

- Screw
- 22.5 mm \times 75.5 mm (diameter \times height) round bottom base
- Marking spot
- Specification certified

For use with 18 mm screw caps

Vial color and material	Clear glass	Amber glass	
Total volume	20 mL	20 mL	
Usable volume	18 mL	18 mL	
Residual volume	0.8 mL	0.8 mL	
Ordering information	Cat. no.	Cat. no.	
100/pack	<u>6ASV20-1</u>	<u>6ASV20-2</u>	
10 x 100/pack	<u>6ASV20-1T</u>	<u>6ASV20-2T</u>	
50 x 100/pack	6ASV20-1F	_	

Looking for caps?

Our 18 mm precision screw caps which are a perfect fit for these vials





10 mL glass crimp headspace vials

Performance level 2 for high-throughput applications

Description

- Crimp
- 22.50 mm \times 46 mm (diameter \times height) round bottom base with beveled edge rim
- Marking spot
- Specification certified

For use with 20 mm crimp caps

Vial color and material	Clear glass	Amber glass
Total volume	10 mL	10 mL
Usable volume	8 mL	8 mL
Residual volume	0.8 mL	0.8 mL
Ordering information	Cat. no.	Cat. no.
100/pack	6ACV10-1R	<u>6ACV10-2R</u>
10 x 100/pack	6ACV10-1RT	<u>6ACV10-2RT</u>
50 x 100/pack	_	6ACV10-2RF



Headspace crimp vials and associated caps (continued) (10 mL – 20 mL vials, 20 mm caps)

20 mL glass crimp headspace vials

Performance level 2 for high-throughput applications

Description

- Crimp
- 22.65 mm × 75 mm (diameter × height) round bottom base with beveled edge rim (6ACV20-1R)
- 23 mm × 75.5 mm (diameter × height) round bottom base with beveled edge rim (6ACV20-1PE, 6ACV20-2PE)
- Marking spot
- Specification certified

For use with 20 mm crimp caps

			Norma Service Service
Vial color and material	Clear glass	Clear glass	Amber glass
Vial diameter and length	22.65 × 75.5	23 × 75.5	23 × 75.5
Total volume	20 mL	20 mL	20 mL
Usable volume	18 mL	18 mL	18 mL
Residual volume	0.8 mL	0.8 mL	0.8 mL
Ordering information	Cat. no.	Cat. no.	Cat. no.
100/pack	6ACV20-1R	6ACV20-1PE*	6ACV20-2PE*
10 x 100/pack	6ACV20-1RT	6ACV20-1PET*	<u>6ACV20-2PET</u> *
50 x 100/pack	6ACV20-1RF	6ACV20-1PEF*	_

* Fit PerkinElmer instruments



Headspace crimp vials and associated caps (continued) (10 mL – 20 mL vials, 20 mm caps)

20 mm crimp caps

Performance level 2 for high-throughput applications

Description

- Crimp closure (20 mm)
- Specification certified

For use with 10 mL and 20 mL crimp headspace vials (with neck size of 20 mm)

Use with 20 mm crimpers and decrimpers

		0			C C C C C C C C C C C C C C C C C C C
	_	_	_	Magnetic	Magnetic
Cap components	_	_	Pressure release	Soft septa	Suitable for high temperature
Cap color and material	Silver aluminum	Silver aluminum	Silver aluminum	Gold steel	Silver steel
Septum color and material	Black butyl/ grey PTFE/ molded PharmaFix	White silicone/ beige PTFE	White silicone/ beige PTFE	Blue silicone/ clear PTFE	Red silicone/ natural PTFE
Septum thickness	3.0 mm	3.2 mm	3.2 mm	3.0 mm	3.0 mm
Septum hardness	50° shore	45° shore	45° shore	40° shore	55° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	6ACC20-PFT	6ACC20-ST1	6APRCC20-ST1	6AMCC20-ST3	6AMCC20-STH
10 x 100/pack	6ACC20-PFTT	6ACC20-ST1T	6APRCC20-ST1T	6AMCC20-ST3T	6AMCC20-STHT
50 x 100/pack	_	6ACC20-ST1F	6APRCC20-ST1F	_	6AMCC20-STHF

Learn more about:

Manual and electronic crimpers and decrimpers





Headspace screw vials and associated caps (20 mL, 18 mm closure)

Screw vial and cap kits

Performance level 2 for high-throughput applications

- Screw thread
- Specification certified
- 22.5 × 75.5 (diameter × height) headspace round bottom base





20 mm stoppers and septa

Performance level 2 for high-throughput applications

Description

• Specification certified

For use with vials (e.g. 10 mL/20 mL crimp vials) with diameter neck size of 20 mm

Product description	Stopper (20 mm)	Septum (20 mm)	Septum (20 mm)
Color and material	Grey bromobutyl	White silicone/beige PTFE	Black butyl/ grey PTFE molded PharmaFix™
Septum thickness	3.0 mm	3.2 mm	3.0 mm
Septum hardness	45° shore	45° shore	50° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.
100/pack	<u>6A20BS</u>	<u>6A20ST1</u>	<u>6A20CBT3</u>
10 x 100/pack	<u>6A20BST</u>	<u>6A20ST1T</u>	_
50 x 100/pack	<u>6A20BSF</u>	<u>6A20ST1F</u>	_



Performance level 2 for high-throughput applications

Description

- Screw (15-425)
- 17 × 60 mm (diameter × height) flat base
- Specification certified Level 100 EPA vials

For use with 15 mm screw caps

These are processed and packages under a strict registered ISO Quality Management System. The products are not certified to EPA standards or pre-cleaned. Every case of product is labeled with its production number and is custody sealed to ensure reliable chain-of-custody.







Vial color and material	Clear glass	Amber glass
Total volume	8 mL	8 mL
Usable volume	6 mL	6 mL
Residual volume	0.8 mL	0.8 mL
Ordering information	Cat. no.	Cat. no.
200/pack	6ASV8EPA-1	6ASV8EPA-2



Performance level 2 for high-throughput applications

Description

- Screw thread (15-425)
- 19 × 65 mm (diameter × height) flat base
- Specification certified Level 100 EPA vials

For use with 15 mm screw caps

These are processed and packages under a strict registered ISO Quality Management System. The products are not certified to EPA standards or pre-cleaned. Every case of product is labeled with its production number and is custody sealed to ensure reliable chain-of-custody.







Vial color and material	Clear glass	Amber glass
Total volume	12 mL	12 mL
Usable volume	11 mL	11 mL
Residual volume	0.8 mL	0.8 mL
Ordering information	Cat. no.	Cat. no.
200/pack	6ASV12EPA-1	6ASV12EPA-2



Performance level 2 for high-throughput applications

Description

- Screw thread (18-400)
- 21 × 70 mm (diameter × height) flat base
- Specification certified Level 100 EPA certified

For use with 18 mm screw caps

These are processed and packages under a strict registered ISO Quality Management System. The products are not certified to EPA standards or pre-cleaned. Every case of product is labeled with its production number and is custody sealed to ensure reliable chain-of-custody.







/		
Vial color and material	Clear glass	Amber glass
Total volume	16 mL	16 mL
Usable volume	15 mL	15 mL
Residual volume	0.8 mL	0.8 mL
Ordering information	Cat. no.	Cat. no.
200/pack	6ASV16EPA-1	6ASV16EPA-2



Performance level 2 for high-throughput applications

Description

- Screw thread (20-400)
- 23 × 85 mm (diameter × height) flat base
- Specification certified Level 100 EPA vials

For use with 20 mm screw caps

These are processed and packages under a strict registered ISO Quality Management System. The products are not certified to EPA standards or pre-cleaned. Every case of product is labeled with its production number and is custody sealed to ensure reliable chain-of-custody.





Vial color and material	Clear glass
Total volume	20 mL
Usable volume	18 mL
Residual volume	0.8 mL
Ordering information	Cat. no.
100/pack 🗳	6ASV20EPA-1



Performance level 2 for high-throughput applications

Description

- Screw thread 24 mm (24-400)
- 28 × 95 mm (diameter × height) flat base
- Specification certified Level 100 EPA vials

For use with 24 mm crimp caps

These are processed and packages under a strict registered ISO Quality Management System. The products are not certified to EPA standards or pre-cleaned. Every case of product is labeled with its production number and is custody sealed to ensure reliable chain-of-custody.







Vial color and material	Clear glass	Amber glass
Total volume	40 mL	40 mL
Usable volume	38 mL	38 mL
Residual volume	0.8 mL	0.8 mL
Ordering information	Cat. no.	Cat. no.
100/pack	6ASV40EPA-1	6ASV40EPA-2



15 mm screw caps

Performance level 2 for high-throughput applications

Description

- Short thread screw closure 15 mm (15-425)
- Specification certified

For use with 8 and 12 mL screw vials (and other vials with screw 15 mm dimensions)

Cap color and material	White PP, close top
Septum color and material	PE foam/PTFE
Septum thickness	_
Septum hardness	75° shore
Ordering information	Cat. no.
100/pack 🗳	6ASC15-CTP



18 mm screw caps

Performance level 2 for high-throughput applications

Description

- Screw closure 18 mm (18-400)
- Specificaiton certified

For use with 20 mL EPA screw vials (and other vials with screw 18 mm dimensions) except for 20 mL headspace vials

Cap color and material	White PP, close top
Septum color and material	PE foam/PTFE
Septum thickness	_
Septum hardness	75° shore
Ordering information	Cat. no.
100/pack	6ASC18-CTP



24 mm screw caps

Performance level 2 for high-throughput applications

Description

- Screw closure 24 mm (24-400)
- Specification certified

For use with 40 mL screw vials (and other vials with screw 24 mm dimensions)

Cap color and material	White PP, close top
Septum color and material	PE foam/PTFE
Septum thickness	_
Septum hardness	75° shore
Ordering information	Cat. no.
100/pack	6ASC24-CTP



Septa for EPA/storage vials

Performance level 2 for high-throughput applications

Description

• Specification certified

For use with screw vials with 20-400 or 24-400 screw thread closure

Product description	Septum (19.5 mm)	Septum (22 mm)
Color and material	Cream silicone/beige PTFE	Clear silicone/beige PTFE
Septum thickness	1.5 mm	2.6 mm
Septum hardness	50° shore	50° shore
Ordering information	Cat. no.	Cat. no.
100/pack	6A20ST20	<u>6A24ST26</u>



Specification certified screw vial and cap kits

Performance level 2 for high-throughput applications

- 2 mL screw vial (9 mm) with short thread screw closure
- Marking spot
- Specification certified





Key attributes	AVCS	AVCS	AVCS	AVCS	AVCS
Vial color and material	Clear glass	Amber glass	Clear glass	Clear glass	Amber glass
Vial total volume	2 mL	2 mL	2 mL	2 mL	2 mL
Cap color and material	Blue PP	Blue PP	Blue PP	Blue PP	Blue PP
Septum color and material	Red silicone/ ivory PTFE	Red silicone/ ivory PTFE	Red PTFE/white silicone/red PTFE	White silicone/ red PTFE	White silicone/ red PTFE
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	<u>6AK80W</u>	<u>6AK82W</u>	<u>6AK86W</u>	<u>6AK92W</u>	<u>6AK94W</u>
Kit vial	<u>6PSV9-1P</u>	6ASV9-2P	6PSV9-1P	<u>6PSV9-1P</u>	6ASV9-2P
Kit closure	6ASC9RT1	6ASC9RT1	6PSC9TST	6ASC9ST1	6ASC9ST1



Performance level 2 for high-throughput applications

- 2 mL screw vial (9 mm) with short thread screw closure
- Marking spot
- Specification certified







Vou attributes	AVCS	AVCS
Key attributes	Pre-slit septa	Soft septa
Vial color and material	Clear glass	Clear glass
Vial total volume	2 mL	2 mL
Cap color and material	Blue PP	Blue PP
Septum color and material	White silicone/blue PTFE slit	Blue silicone/clear PTFE
Ordering information	Cat. no.	Cat. no.
100/pack	<u>6AK95W</u>	<u>6AK599W</u>
Kit vial	<u>6PSV9-1P</u>	<u>6ASV9-1P</u>
Kit closure	6PSC9STS1	6PSC9ST101



Performance level 2 for high-throughput applications

- 2 mL screw vial (9 mm) with short thread screw closure
- Marking spot
- Specification certified









1/	SureStop/AVCS	SureStop/AVCS	SureStop/AVCS
Key attributes	_	_	Pre-slit septa
Vial color and material	Clear glass	Amber glass	Clear glass
Vial total volume	2 mL	2 mL	2 mL
Cap color and material	Blue PP	Blue PP	Blue PP
Septum color and material	White silicone/red PTFE	White silicone/red PTFE	White silicone/blue PTFE slit
Ordering information	Cat. no.	Cat. no.	Cat. no.
100/pack 🗳	<u>6AK592W</u>	<u>6AK594W</u>	<u>6AK595W</u>
Kit vial	6PSV9-1PSS	6PSV9-2PSS	6PSV9-1PSS
Kit closure	<u>6ASC9ST1</u>	6ASC9ST1	6PSC9STS1



Performance level 2 for high-throughput applications

- 2 mL screw vial (9 mm) with short thread screw closure
- Marking spot
- Specification certified







Van attributes	Bonded	Bonded	
Key attributes	Pre-slit septa	_	
Vial color and material	Clear glass	Clear glass	
Vial total volume	2 mL	2 mL	
Cap color and material	Grey PP	Black PP	
Septum color and material	White silicone/red PTFE slit	White silicone/red PTFE	
Ordering information	Cat. no.	Cat. no.	
100/pack	<u>6AK93BW</u>	<u>6AK78BW</u>	
Kit vial	<u>6PSV9-1P</u>	<u>6PSV9-1P</u>	
Kit closure	6PSC9STBS1 6PSC9STB1		



Performance level 2 for high-throughput applications

- 2 mL screw vial (9 mm) with short thread screw closure and for PFAS additionally with 11 mm snap vial and cap
- Marking spot
- Specification certified





Performance level 2 for high-throughput applications

- Assembled 2 mL screw vial (9 mm) with short thread screw closure
- Marking spot
- Specification certified



Vial color and material	Clear glass	Clear glass	Amber glass	
Vial total volume	2 mL	2 mL	2 mL	
Cap color and material	Blue PP	Blue PP	Blue PP	
Septum color and material	Silicone RedRubber/ivory PTFE	Red PTFE/white silicone/red PTFE	Red PTFE/white silicone/red PTFE	
Ordering information	Cat. no.	Cat. no.	Cat. no.	
Ordering information	Cat. no. <u>6AK180W</u>	Cat. no. <u>6AK186W</u>	Cat. no. <u>6AK188W</u>	
<u>^@</u>				



Performance level 2 for high-throughput applications

- Assembled 2 mL screw vial (9 mm) with short thread screw closure
- Marking spot
- Specification certified



Specification certified vial and cap kits, EPA kits, and scintillation kits (continued)

EPA screw vial and cap kits

Performance level 2 for high-throughput applications

Description

- 4 mL 40 mL screw vials with screw closures (13 mm 24 mm)
- Level 100 EPA vials

These are processed and packages under a strict registered ISO Quality Management System. The products are not certified to EPA standards or pre-cleaned. Every case of product is labeled with its production number and is custody sealed to ensure reliable chain-of-custody.

EPA screw vials convenience kits are recommended for discrete water sampling under EPA 40 CFR 136 "Guidelines for Establishing Test Procedures for the Analysis of Pollutants" and EPA 40 CFR 141 "National Interim Primary Drinking Water Regulations: Control of Trihalomethanes in Drinking Water".

	A i i man	AN INCOMENT	(bi)	Carl Contraction of the second	511	Bi I man
Vial color and material	Clear glass	Amber glass	Clear glass	Amber glass	Clear glass	Amber glass
Vial total volume	4 mL (13 mm)	4 mL (13 mm)	8 mL (15 mm)	8 mL (15 mm)	12 mL (15 mm)	12 mL (15 mm)
Cap color and material	White screw cap (PP) (13 mm) close topWhite screw cap (PP) (15 mm) close top					
Septum color and material			PE foam/white	PTFE closed top		
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	6AK4CCT	6AK4ACT	_	_	_	_
200/pack	_	_	6AK8CCT	6AK8ACT	6AK12CCT	6AK12ACT
Kit vial	*	*	6ASV8EPA-1	6ASV8EPA-2	6ASV12EPA-1	6ASV12EPA-2
Kit closure	*	*	6ASC15-CTP	6ASC15-CTP	6ASC15-CTP	6ASC15-CTP

* Not available as single part



EPA screw vial and cap kits (continued)

Performance level 2 for high-throughput applications

Description

- 4 mL 40 mL screw vials with screw closures (13 mm 24 mm)
- Level 100 EPA vials

These are processed and packages under a strict registered ISO Quality Management System. The products are not certified to EPA standards or pre-cleaned. Every case of product is labeled with its production number and is custody sealed to ensure reliable chain-of-custody.

EPA screw vials convenience kits are recommended for discrete water sampling under EPA 40 CFR 136 "Guidelines for Establishing Test Procedures for the Analysis of Pollutants" and EPA 40 CFR 141 "National Interim Primary Drinking Water Regulations: Control of Trihalomethanes in Drinking Water".



Vial color and material	Clear glass	Amber glass	Clear glass	Amber glass	Clear glass
Vial total volume	16 mL (18 mm 18-400)		20 mL (24 mm/24-400)		
Cap color and material	White screw cap (PP) (18 mm) White screw cap (PP) (24 mm), as			assembled	
Septum color and material	PE toam/white PTEE closed top			Clear silicone/white PFTE open top	
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	_	-	6AK20CCTAS	6AK20ACTAS	6AK20COTAS
200/pack	6AK16CCT	6AK16ACT	_	_	_
Kit vial	6ASV16EPA-1	6ASV16EPA-2	6ASV20EPA-1	*	*
Kit closure	6ASC18-CTP	6ASC18-CTP	6ASC24-CTP	6ASC24-CTP	*

* Not available as single part
Specification certified vial and cap kits, EPA kits, and scintillation kit (continued)

EPA screw vial and cap kits (continued)

Performance level 2 for high-throughput applications

Description

- 4 mL 40 mL screw vials with screw closures (13 mm 24 mm)
- Level 100 EPA vials

	and a second	Barrier Contraction	And a summer	tation the monocorrise the monocorrise
Vial color and material	Clear glass	Amber glass	Clear glass	Amber glass
Vial total volume	40 mL (24 mm)			
Cap color and material	White screw cap (PP) (24 mm), assembled		White screw cap (PP) (24 mm)	
Septum color and material	Clear silicone/white PTFE open top		PE foam/white	PTFE closed top
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	6AK40COTAS	6AK40AOTAS	<u>6AK40CCT</u>	<u>6AK40ACT</u>
Kit vial	6ASV40EPA-1	6ASV40EPA-2	6ASV40EPA-1	6ASV40EPA-2
Kit closure	*	*	6ASC24-CTP	6ASC24-CTP

* Not available as single part

Key attributes	Scintillation	
Vial color and material	Clear screw	
Vial total volume	20 mL	
Cap color and material	White closed top screw cap	
Septum color and material	Silver PP foil	
Ordering information	Cat. no.	
5 x 100/pack	<u>6AK20SCIN</u>	

thermofisher.com/surestart

Performance level 3: High performance



When sensitivity is a must

Protect your most valuable samples and deliver consistent, reproducible results for your most demanding analyses

Our Thermo Scientific[™] SureSTART[™] Performance level 3 products are packed in clean rooms to protect them against environmental factors, and contain the lowest amounts/levels of metals, extractables and leachables; ensuring that you can get the sensitivity and selectivity from your most challenging analytes confidently and consistently.

If you need highest performance from your methods, while maintaining high levels of and sample security and integrity, our Performance level 3 products will meet your needs. Select the products with the three waves.

For analytes that are prone to glass adsorption why not try our GOLD-grade glass technology which has been specifically designed for these more challenging polar analytes, as well as our silanized vials and inserts

This offering includes Thermo Scientific[™] SureStop[™] vials, which, when used with 9 mm AVCS caps, ensure an optimal seal every time. The SureStop vial-AVCS cap system is specially designed to prevent screw thread vial failures such as cap tilt, cap deformities, dislodged septa or septa push through, thus prevents injection failures and sample evaporation.

Our Performance level 3 septa have high purity as they have been conditioned to remove all the low-mid boiling volatiles providing the lowest extractables and leachables within the collection. You can also find within this Performance level soft septa options for ultimate needle performance, as these products offer protection for even the most fragile needles with high gauge, and SPME fibers. You can also find our high temperature compatible septa here.

Performance level 3

for high performance applications

- All products within this Performance level are suitable for GC, HPLC/UHPLC, and nominal mass and high-resolution accurate mass (HR-AM) applications
- Headspace vials and caps available from 6 mL 20 mL
- Vials are identified by three waves and a convenient write-on patch as standard
- Vials available as screw, SureStop, snap and crimp
- Vials available in glass, GOLD-grade glass, silanized and TPX
- Vials available as clear or amber glass
- Volume sizes ranging from 0.2 mL to 20 mL covering limited sample volumes to headspace analyses
- Vials with fixed inserts are available
- Caps available as screw, screw AVCS, snap and crimp
- Use Thermo Scientific Manual or Electronic Crimpers and decrimpers for easy application and removal of crimp caps
- LC/GC Certified, MSCERT and MSCERT+ Kits can be found within Performance level 3
- Buy vials and caps in bulk for greater savings

Specification certified

- All Thermo Scientific SureSTART vials are dimensionally verified
- Inspected by automated optical and gauge inspection to ensure critical dimensions and tolerances
- Meet all relevant requirements of US, EU, JPN Pharmacopeia
- Uniform and defect-free

Lot traceable

- 100% traceable through the manufacturing process
- Certificate of Conformance available by lot number upon request

Performance level 3: High performance

16.1	<u>^</u>	
Vials 0.2 mL TPX screw microvial	Caps	
	_	
Glass screw vials	_	
1.4 mL total recovery glass screw vials	_	
1.5 mL total recovery glass screw vials	9 mm screw caps	
1.7 mL high recovery glass screw vials		
2 mL glass screw vials	_	
2 mL GOLD-grade glass screw vials	_	
Glass crimp microvials		
2 mL GOLD-grade glass crimp vial	– 11 mm crimp caps	
2 mL glass crimp vials		
Glass snap microvials	– 11 mm crimp caps	
1.5 mL total recovery glass snap microvials		
High recovery glass snap microvials	11 mm snap caps	
2 mL glass snap vials		
Vial inserts for 2 mL vials	_	
Glass crimp headspace vials	20 mm crimp caps	
Crimpers and	l decrimpers	
Electronic crimper	s and decrimpers	
Kir		
LC/GC certified		
TC		
MSCERT and		
Assembled		
		_



Screw vials and associated caps (<2 mL – 2 mL vials, 9 mm caps)

0.2 mL TPX screw microvial with glass insert

Performance level 3 for high performance analysis

Description

- Short thread screw
- 12 mm × 32 mm (diameter × height) fixed conical glass insert
- No marking spot
- Specification certified

For use with 9 mm screw caps, or 9 mm AVCS screw cap



Want to learn more?





Watch this short microsampling video





It is a transparent plastic (polymethylpentene) that is heat resistant and has excellent resealability.



Screw vials and associated caps (continued) (<2 mL – 2 mL vials, 9 mm caps)

Glass screw microvials

Performance level 3 for high performance analysis

Description

- Short thread screw
- 12 mm × 32 mm (diameter × height) fixed conical insert, flat bottom base
- Marking spot
- Specification certified

Vial color and material	Clear glass	Amber glass	
Total volume	l volume 300 μL 300 μL		
Usable volume	ble volume 250 μL 250 μL		
Residual volume	2 µL	2 μL	
Ordering information	Cat. no.	Cat. no.	
100/pack	6PSV9-03FIVP 6PSV9-03FIVAP		
10 x 100/pack	6PSV9-03FIVPT	6PSV9-03FIVAPT	
50 x 100/pack	6PSV9-03FIVPF	6PSV9-03FIVAPF	



1.5 mL total recovery glass screw microvial

Performance level 3 for high performance analysis

Description

- Short thread screw
- 12 mm × 32 mm (diameter × height) total recovery internal base
- No marking spot
- Specification certified

Vial color and material	Clear glass
Total volume	1.5 mL
Usable volume	1.1 mL
Residual volume	1 µL
Ordering information	Cat. no.
100/pack	<u>6PSV9-TR1</u>
10 x 100/pack	<u>6PSV9-TR1T</u>
50 x 100/pack	<u>6PSV9-TR1F</u>



1.4 and 1.7 mL high recovery glass screw microvial

Performance level 3 for high performance analysis

Description

- Short thread screw
- 12 mm × 32 mm (diameter × height) internal V-base
- No marking spot
- Specification certified

Vial color and material	Clear glass	Clear glass	Clear glass
Total volume	1.4 mL	1.7 mL	1.7 mL
Usable volume	1.0 mL	1.5 mL	1.5 mL
Residual volume	4 μL	3 µL	4 μL
Ordering information	Cat. no.	Cat. no.	Cat. no.
100/pack	6PSV9-CHV1	<u>6PSV9-SV1</u>	<u>6PSV9-V1</u>
10 x 100/pack	-	-	<u>6PSV9-V1T</u>
50 x 100/pack	-	_	<u>6PSV9-V1F</u>



2 mL GOLD-grade glass screw vials

Performance level 3 for high performance analysis

Description

- Short thread screw
- 12 mm × 32 mm (diameter × height), flat bottom base
- Marking spot
- Specification certified

Vial color and material	SureStop, GOLD-grade glass
	Clear glass
Total volume	2 mL
Ordering information	Cat. no.
100/pack	<u>6PSV9-1PG</u>
10 x 100/pack	6PSV9-1PGT
50 x 100/pack	6PSV9-1PGF



Screw vials and associated caps (continued) (<2 mL - 2 mL vials, 9 mm caps)

2 mL glass screw vials

Performance level 3 for high performance analysis

Description

- Screw
- 12 mm x 32 mm (diameter x height) flat bottom base
- Marking spot
- Specification certified

For use with 9 mm screw caps, or 9 mm AVCS screw caps

Vial color and material	_	Silianized	SureStop	SureStop
vial color and material	Clear glass	Clear glass	Clear glass	Amber glass
Total volume	2 mL	2 mL	2 mL	2 mL
Usable volume	1.5 mL	1.5 mL	1.5 mL	1.5 mL
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	<u>6PSV9-1P</u>	<u>6PSV9-S1P</u>	6PSV9-1PSS	6PSV9-2PSS
10 x 100/pack	<u>6PSV9-1PT</u>	_	6PSV9-1PSST	6PSV9-2PSST
50 x 100/pack	6PSV9-1PF	_	6PSV9-1PSSF	6PSV9-2PSSF

Need a smaller volume?

Why not use with our polyspring glass inserts





Screw vials and associated caps (continued) (<2 mL - 2 mL vials, 9 mm caps)

9 mm screw caps

Performance level 3 for high-throughput applications

Description

- Short thread screw
- Specification certified

Con componente	AVCS cap	AVCS cap	AVCS cap
Cap components	_	Pre-slit septa	_
Cap color and material	Blue PP	Blue PP	Blue PP
Septum color and material	Red PTFE/ white silicone/red PTFE	White silicone/blue PTFE	White silicone/red PTFE
Septum hardness	45° shore	54° shore	54° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.
100/pack	6PSC9TST	6PSC9STS1	6PSC9ST1
10 x 100/pack	6PSC9TSTT	6PSC9STS1T	6PSC9ST1T
50 x 100/pack	6PSC9TSTF	6PSC9STS1F	6PSC9ST1F



Screw vials and associated caps (continued) (<2 mL - 2 mL vials, 9 mm caps)

9 mm screw caps (continued)

Performance level 3 for high-throughput applications

Description

- Short thread screw
- Specification certified

		8	
	AVCS cap	AVCS cap	AVCS cap
Cap components	Pre-slit septa	_	_
	Soft septa	Soft septa	_
Cap color and material	Blue PP	Blue PP	Red PP
Septum color and material	Blue silicone/clear PTFE	Blue silicone/clear PTFE	Red PTFE/ white silicone/red PTFE
Septum hardness	30° shore	30° shore	45° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.
100/pack	6PSC9ST101X	6PSC9ST101	6PSC9TSTR
10 x 100/pack	_	_	6PSC9TSTRT
50 x 100/pack	_	_	6PSC9TSTRF



9 mm screw caps (continued)

Performance level 3 for high-throughput applications

Description

- Short thread screw
- Specification certified
- Screw AVCS technology





Screw vials and associated caps (continued) (<2 mL – 2 mL vials, 9 mm caps)

9 mm screw caps (continued)

Performance level 3 for high-throughput applications

Description

- Short thread screw
- Specification certified

For use with <2 mL - 2 mL screw vials

Con componente	AVCS cap	AVCS cap	Bonded cap	Bonded cap
Cap components	Pre-slit septa	-	Pre-slit septa	-
Cap color and material	Red PP	Red PP	Grey PP	Black PP
Septum color and material	White silicone/blue PTFE	White silicone/red PTFE	White silicone/red PTFE	White silicone/red PTFE
Septum thickness	1 mm	1 mm	1 mm	1 mm
Septum hardness	54° shore	54° shore	54° shore	54° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	6PSC9STS1R	6PSC9ST1R	6PSC9STBS1	6PSC9STB1
10 x 100/pack	6PSC9STS1RT	6PSC9ST1RT	6PSC9STBS1T	6PSC9STB1T
50 x 100/pack	-	6PSC9ST1RF	6PSC9STBS1F	6PSC9STB1F

thermofisher.com/surestart



9 mm screw caps (continued)

Performance level 3 for high-throughput applications

Description

- Short thread screw
- Specification certified

Con componente	AVCS cap
Cap components	Magnetic cap
Cap color and material	Blue PP with gold magnetic tinplate cover
Septum color and material	White silicone/red PTFE
Septum thickness	1 mm
Septum hardness	54° shore
Ordering information	Cat. no.
100/pack	6PMSC9ST1



Crimp vials and associated caps (<2 mL – 2 mL, 11 mm caps)

Glass crimp microvials

Performance level 3 for high performance analysis

Description

- Crimp
- 6 mm x 32 mm (diameter x height) for teh round bottom and conical 8 mm crimp vials
- 12 mm x 32 mm (diameter x height) fixed conical insert, flat bottom base
- Marking spot
- Specification certified

For use with 11 mm crimp caps; the round and conical crimp vials with 8 mm crimp caps





2 mL GOLD-grade crimp vials

Performance level 3 for high performance analysis

Description

- Crimp
- 12 mm x 32 mm (diameter x height)
- Marking spotSpecification certified

For use with 11 mm crimp caps

	GOLD-grade glass
Vial color and material	Clear glass
Total volume	2 mL
Usable volume	1.5 mL
Ordering information	Cat. no.
100/pack	<u>6PCV11G</u>

Need a smaller volume?

Why not use with our glass inserts





Crimp vials and associated caps (continued) (<2 mL – 2 mL, 11 mm caps)

2 mL glass crimp vials

Performance level 3 for high performance analysis

Description

- Crimp
- 12 mm × 32 mm (diameter × height)
- Marking spot
- Specification certified

For use with 11 mm crimp caps



Need a smaller volume?

Why not use with our glass inserts





11 mm crimp caps

Performance level 3 for high performance analysis

Description

- Crimp closure (11 mm)
- Specification certified

For use with <2 mL – 2 mL crimp vials, or <2 mL – 2 mL snap vials

Use with 11 mm crimpers and decrimpers

Cap color and material	Silver aluminum	Silver magnetic steel
Septum color and material	Red PTFE/white silicone/red PTFE	White silicone/red PTFE
Septum thickness	1 mm	1 mm
Septum hardness	45° shore	57° shore
Ordering information	Cat. no.	Cat. no.
100/pack	6PCC11TST	6PCCMST15

Learn more about:

Manual and electronic crimpers and decrimpers





Crimp vials and associated caps (continued) (<2 mL - 2 mL, 11 mm caps)

11 mm crimp caps (continued)

Performance level 3 for high performance analysis

Description

- Crimp closure (11 mm)
- Specification certified

For use with <2 mL – 2 mL crimp vials, or <2 mL – 2 mL snap vials

Use with 11 mm crimpers and decrimpers

Cap color and material	Silver aluminum	Silver aluminum	Silver magnetic steel	
Septum color and Blue silicone/clear PTFE, soft se		Blue silicone/PTFE pre-slit septa	Blue silicone/clear PTFE, soft septa, pre-slit	
Septum thickness	1 mm	1 mm	1 mm	
Septum hardness 30° shore		30° shore	30° shore	
Ordering information	Cat. no.		Cat. no.	
100/pack	6PCC11ST101	6PCC11ST101X	6PCCMST101X	



Snap vials and associated caps (<2 mL – 2 mL vials, 11 mm caps)

Glass snap microvials

Performance level 3 for high performance analysis

Description

- Snap
- 11 mm × 32 mm (diameter × height) fixed conical insert, flat bottom base
- Marking spot
- Specification certified

For use with 11 mm snap caps or 11 mm crimp caps

Vial color and material	Clear glass	Amber glass
Total volume	300 µL	300 µL
Usable volume	250 μL	250 μL
Residual volume	4 μL	4 µL
Ordering information	Cat. no.	Cat. no.
100/pack	6PRV11-03FIVP	6PRV1103FIVAP
10 x 100/pack	6PRV11-03FIVPT	6PRV1103FIVAPT
50 x 100/pack	6PRV11-03FIVPF	6PRV1103FIVAPF



Snap vials and associated caps (continued) (<2 mL - 2 mL vials, 11 mm caps)

1.5 mL total recovery glass snap microvials

Performance level 3 for high performance analysis

Description

- Snap
- 12 mm × 32 mm (diameter × height) total recovery internal base
- No marking spot
- Specification certified

For use with 11 mm snap caps

Vial color and material	Clear glass
Total volume	1.5 mL
Usable volume	1.1 mL
Residual volume	1 µL
Ordering information	Cat. no.
100/pack	<u>6PRV11-TR1</u>
10 x 100/pack	<u>6PRV11-TR1T</u>
50 x 100/pack	_



High recovery glass snap microvials

Performance level 3 for high performance analysis

Description

- Snap
- 12 mm × 32 mm (diameter × height) internal V-base
- No marking spot
- Specification certified

For use with 11 mm snap caps

Vial color and material	Silanized glass	Clear glass	Clear glass	
Total volume	1.7 mL	1.7 mL	1.5 mL	
Usable volume 1.5 mL		1.5 mL	1.2 mL	
Residual volume	4 μL	4 μL	4 µL	
Ordering information	Cat. no.	Cat. no.	Cat. no.	
100/pack	<u>6PRV11-S1V</u>	<u>6PRV11-1V</u>	<u>6PRV11-15V</u>	
10 x 100/pack	-	-	<u>6PRV11-15VT</u>	
50 x 100/pack	-	-	_	



Snap vials and associated caps (continued) (<2 mL - 2 mL vials, 11 mm caps)

2 mL glass snap vials

Performance level 3 for high performance analysis

Description

- Snap
- 12 mm × 32 mm (diameter × height)
- Marking spot
- Specification certified

For use with 11 mm snap caps



Need a smaller volume?

Why not use with our glass inserts





Snap vials and associated caps (continued) (<2 mL - 2 mL vials, 11 mm caps)

11 mm snap cap

Performance level 3 for high performance analysis

Description

- Snap closure (11 mm)
- Specification certified

For use with <2 mL and 2 mL snap vials

Key attributes	Pre-slit septa	_	_	Star pre-slit septa
Cap color and material	Blue PE	Blue PE Blue PE		Clear PE
Septum color and material	White silicone/blue PTFE	White silicone/red PTFE	Blue silicone/clear PTFE, soft	White silicone/red PTFE
Septum thickness	1 mm	1 mm 1 mm		1 mm
Septum hardness	Septum hardness		45° shore	54° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	6PRC11STS1	6PRC11ST1	6PRC11ST101	6PRC11STS1X
10 x 100/pack	6PRC11STS1T	PRC11ST1T	6PRC11ST101T	6PRC11STS1XT
50 x 100/pack	6PRC11STS1F	6PRC11ST1F	6PRC11ST101F	6PRC11STS1XF



Snap vials and associated caps (continued) (<2 mL - 2 mL vials, 11 mm caps)

11 mm snap cap (continued)

Performance level 3 for high performance analysis

Description

- Snap closure (11 mm)
- Specification certified

For use with <2 mL and 2 mL snap vials

	8	8	8	8	
Key attributes	Pre-slit septa	_	_	_	
Cap color and material	Red PE	Red PE	Red PE	Red PE	
Septum color and Red silicone/blue P		White silicone/red PTFE	Blue silicone/clear PTFE, soft	Red PTFE/white silicone/ red PTFE	
Septum thickness	1.3 mm	1.3 mm 1.0 mm		1.0 mm	
Septum hardness	54° shore	54° shore	45° shore	50° shore	
Ordering information	nformation Cat. no. Cat. n		Cat. no.	Cat. no.	
100/pack	6PRC11STS1R	6PRC11ST1R	6PRC11ST101R	6PRC11TST1R	
10 x 100/pack	6PRC11STS1RT	6PRC11ST1RT	6PRC11ST101RT	_	
50 x 100/pack	6PRC11STS1RF	6PRC11ST1RF	6PRC11ST101RF	_	

97



Snap vials and associated caps (continued) (<2 mL - 2 mL vials, 11 mm caps)

11 mm snap cap (continued)

Performance level 3 for high performance analysis

Description

- Snap closure (11 mm)
- Specification certified

For use with <2 mL and 2 mL snap vials

		8		
Key attributes	Pre-slit	Pre-slit	Pre-slit	
Cap color and material	Green PE	Yellow PE	Clear PE	
Septum color and material	White silicone/blue PTFE	White silicone/blue PTFE	White silicone/blue PTFE	
Septum thickness	45° shore	45° shore	45° shore	
Septum hardness	1.0 mm	1.0 mm	1.0 mm	
Ordering information	Cat. no.	Cat. no.	Cat. no.	
100/pack	6PRC11STS1G	6PRC11STS1Y	6PRC11STS1C	



Inserts for 2 mL vials

Performance level 3 for high-throughput applications

Description

- 6 mm × 31 mm (diameter × height)
- No marking spot
- Specification certified

For use with 2 mL screw vials, 2 mL snap vials or 2 mL crimp vials



Watch this short microsampling video

		Ð	J.	J.		
	GOLD-grade glass	Deactivated/ silanized glass	_	GOLD-grade glass	_	_
Insert color and material	0.2 mL clear conical glass insert	0.3 mL clear conical glass insert, with PE polyspring	0.3 mL conical glass insert, with PE polyspring	0.3 mL conical borosilicate glass insert, with PE polyspring	0.4 mL clear conical glass insert, with pulled point	0.4 mL clear conical glass insert, with precision point
Total volume	200 µL	300 µL	300 µL	300 µL	400 µL	400 µL
Usable volume	150 µL	250 µL	250 µL	250 µL	350 µL	350 µL
Residual volume	2 µL	1 µL	4 µL	4 µL	4 μL	2 µL
Height	31 mm	30 mm	30 mm	30 mm	31 mm	31 mm
Outer diameter	6 mm	6 mm	6 mm	6 mm	6 mm	6 mm
Base style	Conical base	Conical base	Conical base	Conical base	Conical base	Conical base
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	_	6PME03C1SSP	6PME03C1SP	6PME03C1SPG	6PME04C1	6PME04CPR1
10 x 100/pack	6PME02CG	6PME03C1SSPT	6PME03C1SPT	_	6PME04C1T	_
50 x 100/pack	_	6PME03C1SSPF	6PME03C1SPF	—	6PME04C1F	_

thermofisher.com/surestart





Watch this short microsampling video

Inserts for 2 mL vials

Performance level 3 for high-throughput applications

Description

- 6 mm × 31 mm (diameter × height)
- No marking spot
- Specification certified

For use with 2 mL screw vials, 2 mL snap vials or 2 mL crimp vials

	_	Blue ring	_	Silanized
Insert color and material	0.4 mL clear flat bottom glass insert	0.4 mL clear flat bottom glass insert,	0.5 mL clear flat bottom glass insert	0.5 mL clear flat bottom glass insert
Total volume	400 µL	400 µL	500 µL	500 µL
Usable volume	250 µL	250 µL	450 µL	450 µL
Residual volume	esidual volume 12 µL		25 µL	25 µL
Height	31 mm	31 mm	31 mm	31 mm
Outer diameter	5.6 mm	5.6 mm	6 mm	6 mm
Base style	Flat bottom	Flat bottom	Flat bottom	Flat bottom
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.
500/pack	6PME04F1*	6PME04F1BR*	<u>6PME05F1</u>	6PME05FS1

*Contact your local sales representative to order



Headspace crimp vials and associated caps (6 mL – 20 mL vials, 20 mm caps)

6 mL, 9.5 mL, 10 mL and 20 mL glass crimp headspace vials

Performance level 3 for high performance analysis

Description

- Crimp (20 mm)
- Marking spot
- Specification certified

For use with 20 mm crimp caps

		Real	serno Scriific.		
Vial color and material	Clear glass	Clear glass, no marking spot, inner V-bottom, high recovery	Clear glass	Clear glass	Clear glass
Total volume	6 mL	9.5 mL	10 mL	20 mL	20 mL
Usable volume	5 mL	9.5 mL	8 mL	18 mL	18 mL
Residual volume	0.8 mL	0.08 mL	0.8 mL	0.8 mL	0.8 mL
Dimensions	21.75 x 38 mm	22.65 x 45.2 mm	22.75 x 46 mm	22.75 x 75.0 mm	22.75 x 75.0 mm
Rim and base style	Square rim, flat bottom	Square rim, flat bottom	Beveled rim, flat bottom	Beveled rim, flat bottom	Beveled rim, round bottom
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	6PCV6-1F	6PCV10-V1	6PCV10-1F	<u>6PCV20-1F</u>	<u>6PCV20-1R</u>
10 x 100/pack	6PCV6-1FT	_	<u>6PCV10-1FT</u>	<u>6PCV20-1FT</u>	6PCV20-1RT
50 x 100/pack	6PCV6-1FF	_	_	6PCV20-1FF	6PCV20-1RF



Headspace crimp vials and associated caps (continued) (6 mL – 20 mL vials, 20 mm caps)

8 mm crimp caps

Performance level 3 for high performance analysis

Description

- Crimp closure (8 mm)
- Specification certified

For use with <2 mL crimp vials (with neck size of 8 mm)

Use with 8 mm crimpers and decrimpers

Cap color and material	Silver aluminum	
Septum color and material	Blue silicone/clear PTFE; soft	
Septum thickness	1 mm	
Septum hardness	30° shore	
Ordering information	Cat. no.	
100/pack	6PCC8ST101	



Headspace crimp vials and associated caps (continued) (6 mL – 20 mL vials, 20 mm caps)

18 mm precision screw caps

Performance level 3 for high performance analysis

Description

- Screw thread closure
- Specification certified

For use with 10 mL and 20 mL screw top headspace vials

	Magnetic	Magnetic
Cap color and material	Silver steel	Silver steel
Septum color and material	Blue silicone/clear PTFE; soft	Red silicone/natural PTFE; high temperature
Septum thickness	2 mm	3 mm
Septum hardness	45° shore	45° shore
Ordering information	Cat. no.	Cat. no.
100/pack	6PMSC18-ST2	6PMSC18-STH
10 x 100/pack	6PMSC18-ST2T	6PMSC18-STHT



20 mm crimp caps

Performance level 3 for high performance analysis

Description

- Crimp closure (20 mm)
- Specification certified

For use with 10 mL and 20 mL crimp headspace vials (with neck size of 20 mm)

Use with 20 mm crimpers and decrimpers

	0				
	_	Magnetic	Magnetic	Magnetic for SPME	Magnetic
Cap color and material	Silver aluminum	Red aluminum/ magnetic tinplate	Silver aluminum/ magnetic tinplate	Blue aluminum/ magnetic tinplate	Red aluminum/ magnetic tinplate
Septum color and material	Blue silicone/ clear PTFE; soft	Blue silicone/ clear PTFE; soft	Red silicone/ natural PTFE; high temperature	White silicone/ blue PTFE	Grey chlorobutyl/ black PTFE
Septum thickness	3 mm	3 mm	3 mm	3 mm, 1.5 mm at thinned area	3 mm
Septum hardness	45° shore	45° shore	54° shore	54° shore	50° shore
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	6PCC20-ST3	6PBCC20-ST3	6PBCC20-STH	6PBCC20-STME	6PBCC20-CBT3
10 x 100/pack	6PCC20-ST3T	6PBCC20-ST3T	6PBCC20-STHT	6PBCC20-STMET	_
50 x 100/pack	6PCC20-ST3F	6PBCC20-ST3F	_	6PBCC20-STMEF	_

Learn more about:

Manual and electronic crimpers and decrimpers





Specification certified, LC/GC certified, MSCERT and MSCERT+ kits

1. Specification certified kits

For everyday analysis

• Tested and certified for up to 15 critical physical specifications

2. LC/GC certified kits

For chromatographic analysis

- Tested and certified for up to 15 critical physical specifications
- Tested and certified using LC-UV and GC-FID to ensure that there are no residual manufacturing agents present in the vial
- A certificate is provided with each kit

3. MSCERT and MSCERT+ kits

For use with mass spectrometry systems

- Our mass spec certified vials carry our highest level of certification and are recommended for low adsorption
- Tested and certified for up to 15 critical physical specifications
- Tested using LC-MS and GC-MS for low contamination
- Certification comes with the kit
- MSCERT+ kits are pre-cleaned and certified for particle count
 - Highly recommended for direct injection analysis (DIA)

	MSCERT	MSCERT+
Proprietary cleaning process to reduce particulates	-	+
Packaged in cleanroom conditions	-	+
Cleanest product available on the market	-	+
Vial/closure combination tested by GC/MS and LC/MS	+	+
Batch specific test certificate with MS-chromatograms	+	+
Closures contain very soft ultra-low bleed silicone septa with PTFE layer or bonded caps	+	+
Optimised for trace analysis	+	+



Specification certified, LC/GC certified, MSCERT and MSCERT+ kits (continued)

Specification certified screw vial and cap kits

Performance level 3 for high performance analysis

Description

- Short thread screw kit
- 12 mm × 32 mm (diameter × height) fixed conical glass insert
- No marking
- Specification certified

For use with short thread screw cap closure

	Bonded caps	
Key attributes	TPX vials	
	0.2 mL with fixed glass insert	
Vial color and material	Amber TPX	
Vial total volume	200 µL	
Vial usable volume	150 μL	
Vial residual volume	1 µL	
Cap color and material	Black screw cap	
Septa color and material	White silicone/red PTFE	
Septa thickness	1 mm	
Ordering information	Cat. no.	
100/pack	<u>6PK1655</u> *	
Kit vial	<u>60180-1655</u>	
Kit closure	6PSC9STB1	

*Recommended for Thermo Scientific[™] Vanquish[™] Neo Systems



Specification certified, LC/GC certified, MSCERT and MSCERT+ kits (continued)

Specification certified screw vial and cap kits (continued)

Performance level 3 for high performance analysis

Description

- Short thread screw kit
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- Specification certified

For use with short thread screw cap closure

	GOLD-grade glass	
Key attributes	SureStop vials	
	AVCS caps	
Vial total volume	2 mL	
Vial color and material	Clear glass	
Cap color and material	Blue screw cap (PP)	
Septa color and material	White silicone/red PTFE	
Septa thickness	1 mm	
Ordering information	Cat. no.	
100/pack	6PKG592W	
Kit vial	6PSV9-1PG	
Kit closure	<u>6PSC9ST1</u>	





Analyzing polar compounds/compounds prone to glass adsorption?

We recommend using our GOLD-grade glass vials



Specification certified, LC/GC certified, MSCERT and MSCERT+ kits (continued)

LC/GC certified kits: <2 mL vials with 9 mm caps

Performance level 3 for high performance analysis

Description

- Short thread screw kit
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- LC/GC certified

For use with short thread screw cap closure

Key attributes	Bonded caps	Bonded caps
	Pre-slit septa	Pre-slit septa
Vial total volume	1.5 mL total recovery vials	0.3 mL fused insert vial
Vial color and material	Clear glass	Clear glass
Cap color and material	Grey screw cap (PP)	Grey screw cap (PP)
Septa color and material	White silicone/red PTFE	White silicone/red PTFE
Septa thickness	1 mm	1 mm
Ordering information	Cat. no.	Cat. no.
100/pack	<u>6PCK993</u> <u>6PCK71LVW</u>	
Kit vial	6PSV9-TR1	6PSV9-03FIVP
Kit closure	6ASC9STBS1	6ASC9STBS1


LC/GC certified kits: 2 mL vials with 9 mm caps

Performance level 3 for high performance analysis

Description

- Short thread screw kit
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- LC/GC certified

For use with short thread screw cap closure

Kov ettributee	Bonded caps	Bonded caps	
Key attributes	Pre-slit septa	Pre-slit septa	
Vial total volume	2 mL	2 mL	
Vial color and material	Clear glass	Amber glass	
Cap color and material	Grey screw cap (PP)	Grey screw cap (PP)	
Septa color and material	White silicone/red PTFE	White silicone/red PTFE	
Septa thickness	1 mm	1 mm	
Ordering information	Cat. no.	Cat. no.	
100/pack	<u>6PCK93W</u>	6PCK76W	
Kit vial	<u>6PSV9-1P</u>	<u>6ASV9-2P</u>	
Kit closure	6PSC9STBS1	6PSC9STBS1	

thermofisher.com/surestart



LC/GC certified kits: 2 mL vials with 9 mm caps (continued)

Performance level 3 for high performance analysis

6PSC9STS1

Description

- Short thread screw kit
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- LC/GC certified

For use with short thread screw cap closure



6PSC9STS1

6ASC9ST1

6ASC9ST1

Kit closure



LC/GC certified assembled kits: 2 mL vials with 9 mm caps

Performance level 3 for high performance analysis

Description

- Short thread screw kit
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- LC/GC certified

For use with short thread screw cap closure

	Bonded caps	Bonded caps	
Key attributes	Pre-slit septa	Pre-slit septa	
Vial total volume	2 mL	2 mL	
Vial color and material	Clear glass	Amber glass	
Cap color and material	Grey screw cap (PP)	Grey screw cap (PP)	
Septa color and material	White silicone/red PTFE	White silicone/red PTFE	
Septa thickness	1 mm	1 mm	
Ordering information	Cat. no.	Cat. no.	
100/pack	6PCK193W	<u>6PCK176W</u>	
Kit vial	<u>6PSV9-1P</u>	6ASV9-2P	
Kit closure	6PSC9STBS1	6PSC9STBS1	



MSCERT kits

Performance level 3 for high performance analysis

Description

- Short thread screw kit
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- LC-MS/GC-MS certified

For use with short thread screw cap closure



Key attributes	AVCS caps	AVCS caps	AVCS caps AVCS caps	
	_	_	Pre-slit septa	Pre-slit septa
Vial total volume	2 mL	2 mL	2 mL	2 mL
Vial color and material	Clear glass	Amber glass	Clear glass	Amber glass
Cap color and material	Blue screw cap (PP)			
Septa color and material	Blue silicone/ clear PTFE septa			
Septa thickness	1 mm	1 mm	1 mm 1 mm	
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	6PMSCK534W	6PMSCK535W	6PMSCK540W	6PMSCK541W
Kit vial	6PSV9-1PSS	6PSV9-2PSS	6PSV9-1PSS	6PSV9-2PSS
Kit closure	6PSC9ST101	6PSC9ST101	6PSC9ST101X	6PSC9ST101X



MSCERT kits (continued)

Performance level 3 for high performance analysis

Description

- Short thread screw kit
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- LC-MS/GC-MS certified

For use with short thread screw cap closure



113

thermofisher.com/surestart



MSCERT+ kits

Performance level 3 for high performance analysis

Description

- Short thread screw kit
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- MSCERT+ certified and pre-cleaned

For use with short thread screw cap closure

	30			
	SureStop vials	SureStop vials	SureStop vials	SureStop vials
Key attributes	AVCS caps	AVCS caps	AVCS caps	AVCS caps
	_	_	Pre-slit septa	Pre-slit septa
Vial total volume	2 mL	2 mL	2 mL	2 mL
Vial color and material	Clear glass	Amber glass	Clear glass	Amber glass
Cap color and material	Blue screw cap	Blue screw cap	Blue screw cap	Blue screw cap
Septa color and material	Blue silicone/clear PTFE	Blue silicone/clear PTFE	Blue silicone/clear PTFE	Blue silicone/clear PTFE
Septa thickness	1 mm	1 mm	1 mm	1 mm
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.
100/pack	6PMCK34W	6PMCK35W	6PMCK40W	6PMCK41W
Kit vial	6PSV9-1PSS	6PSV9-2PSS	6PSV9-1PSS	6PSV9-2PSS
Kit closure	6PSC9ST101	6PSC9ST101	6PSC9ST101X	6PSC9ST101X



MSCERT+ kits (continued)

Performance level 3 for high performance analysis

Description

- Short thread screw kit
- 12 mm × 32 mm (diameter × height) flat bottom base
- Marking spot
- MSCERT+ certified and pre-cleaned

For use with short thread screw cap closure

	20		20	300	
	_	_	Fused-insert	Fused-insert	
Key attributes	Bonded	Bonded	Bonded	Bonded	
	_	_	_	Pre-slit septa	
Vial total volume	2 mL	2 mL	0.3 mL	0.3 mL	
Vial color and material	Clear glass	Amber glass	Clear glass	Clear glass	
Cap color and material	Blue screw cap	Blue screw cap	Blue screw cap	Grey screw cap	
Septa color and material	Clear silicon/clear PTFE	Clear silicon/clear PTFE	Clear silicon/clear PTFE	White silicon/red PTFE	
Septa thickness	1 mm	1 mm	1 mm	1 mm	
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.	
100/pack	6PMCK341W	6PMCK351W	6PMCK30LVW	6PMCK36LVW	
Kit vial	<u>6PSV9-1P</u>	6ASV9-2P	6PSV9-03FIVP	6PSV9-03FIVP	
Kit closure	*	*	*	6PSC9STBS1	

* Not available as single part

thermofisher.com/surestart



MSCERT+ kits (continued)

Performance level 3 for high performance analysis

Description

- Total recovery vial
- Short thread screw vial
- 12 mm \times 32 mm (diameter \times height) flat bottom base
- MSCERT+ certified and pre-cleaned

For use with short thread screw cap closure

	Total recovery
Key attributes	Bonded
	Pre-slit septa
Vial total volume	1.5 mL
Vial color and material	Clear glass
Cap color and material	Grey screw cap
Septa color and material	White silicon/red PTFE
Septa thickness	1 mm
Ordering information	Cat. no.
100/pack	6PMCK39TR
Kit vial	<u>6PSV9-TR1</u>
Kit closure	6PSC9STBS1



EPA certified assembled kits: 40 mL with 24 mm caps

Performance level 3 for high performance analysis

Description

- Screw thread 24 mm (24-400)
- 28 mm × 95 mm (diameter × height) flat bottom base
- Processed and packaged under a registered ISO Quality Management System
- Laboratory certified to meet U.S. EPA Super Fund Standards in accordance with the latest edition of EPA's "Specifications and Guidance for Contaminant Free Sample Containers"
- Every case contains a Certificate of Analysis and is custody sealed to ensure reliable chain-of-custody



Vial description	40 mL (24 mm) screw glass vial
Vial color and material	Clear
Cap description	Bonded white screw cap (24-400) (PP), open top
Septum color and material	White silicone/clear PTFE
Septum thickness	3 mm
Septum hardness	50° shore
Ordering information	Cat. no.
72/pack	6ACK40COTAS

thermofisher.com/surestart



TOC certified screw vial and cap kits

Performance level 3 for high performance analysis

Description

- TOC certification (20 ppb)
- TOC certification (10 ppb)

Our low-level certified vials for Total Organic Carbon testing and sampling are manufactured, tested and packaged by exacting standards. Thermo Scientific[™] TOC Certified Containers are certified to contribute <10ppb or < 20ppb TOC as background.



Vial description	40 mL (24 mm) screw glass vial			
Vial color and material	Clear			
Cap description	Bonded white screw cap (24-400) (PP), open top			
Septum color and material	White silicone/clear PTFE			
Septum thickness	3 mm			
Septum hardness	50° shore			
Certification level	TOC certification (20 ppb) TOC certification (10 ppb)			
Ordering information	Cat. no. Cat. no.			
72/pack	<u>6PK40TOC20</u> <u>6PK40TOC10</u>			

SureSTART vials and caps accessories

Manual crimpers and decrimpers

Manual crimpers and decrimpers

Achieve secure, repeatable crimps or remove seals with minimized risk of damage

Use Thermo Scientific[™] SureSTART[™] vial crimpers and decrimpers to manually attach or remove crimp caps from vials, respectively. These manual crimpers and decrimpers are available in 8 mm, 11 mm, 13 mm, and 20 mm sizes and allow you to easily seal or remove crimp caps reliably.*





Product description	Red manual crimper				Stainless steel manual crimper**
Suitable for	8 mm crimp caps	' 11 mm crimp caps 13 mm crimp caps 20 mm crimp caps			
Ordering information	Cat. no.	Cat. no. Cat. no. Cat. no. Cat. no.		Cat. no.	
1/pack	60180-CR8	<u>60180-CR11</u>	60180-CR13	60180-CR20	60180-CR20SS

**Crimper can be sterilized, for clean room applications



Product description	_	Black manual decrimper	Black manual decrimper	_	Black manual decrimper
Suitable for	_	11 mm crimp caps	13 mm crimp caps	_	20 mm crimp caps
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.	Cat. no.
1/pack	_	60180-DCR11	60180-DCR13	—	60180-DCR20

*These crimper are not for flip top/flip off closures. Further specials are available on request or see our selection of electronic crimper on the following page.

Electronic crimpers and decrimping tools

Electronic crimpers and decrimpers

Our electronic Thermo Scientific crimper portfolio includes tools for 8 mm, 11 mm, 13 mm, and 20 mm crimp caps.

The tools provide all important settings like actual crimp power at one glance. The hand-held crimpers and decrimpers allow crimping of vials with aluminum, pressure release and bi-metal caps while remaining in most sample trays.

The crimp head selection includes also special crimp heads for 13 mm and 20 mm flip-off caps, further specials are available on request.

Attach or remove crimp vial seals with high sample security with a simple, one-handed push of a button.

Electronic hand-held crimpers and decrimpers

The battery charge icon on the color screen of the hand-held tools changes to red when battery is low. Each hand-held tool comes with fully rechargeable lithium ion battery and universal power supply/recharger and international plug adapters.

For steel caps and/or high numbers of crimp or decrimp processes per day we recommend the Thermo Scientific[™] High-Power Crimp Station as it provides high crimping force independent from any battery charge status.



Versatile and programmable crimp station

Electronic crimpers and decrimpers features and benefits

- Tools available for use with 8 mm, 11 mm, 13 mm, and 20 mm crimp vial caps
- Available as handheld and high-power models
- These electronic vial crimpers also feature adjustable settings for best crimp results and a motor with extended lifetime and no particle emission
- Interchangeable crimper and decrimper jaw sets for Programmable Electronic High-Power Crimp Stations
- One hand operation with a simple push of a button
- Error message feedback after the incorrect crimping process
- Adjustable settings for best crimp results
- Actual crimp power setting displayed on the color screen.
- 8 different languages available-EN, CN, JA, DE, FR, ES, IT, KO
- · Motor with extended lifetime and no particle emission
- Free hands for faster crimping operations with the adjustable Thermo Scientific[™] Accessory Base for Programmable Electronic High-Power Crimp Stations. (ECRH-STAND)
- Each High-Power Crimper comes with 12-volt DC supply with power cord
- Crimp and Decrimp Heads for the High-Power Crimper are included in the kits or available separately

Electronic crimpers and decrimping tool (continued)

Electronic hand-held battery-operated crimper (black) Generation 4



Product description	Electronic hand-held battery-operated crimper (black). Generation 4						
Suitable for	8 mm crimp caps 11 mm crimp caps 13 mm crimp caps 20 mm crimp caps						
Ordering information	Cat. no. Cat. no. Cat. no. Cat. no.						
1/pack	<u>60180-ECR8</u>	<u>60180-ECR11</u>	<u>60180-ECR13</u>	<u>60180-ECR20</u>			

Electronic hand-held battery-operated decrimper (black) Generation 4

Product description	Electronic hand-held battery-operated decrimper (black). Generation 4					
Suitable for	 — 11 mm crimp caps 13 mm crimp caps 20 mm crimp caps 					
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.		
1/pack	_	60180-EDCB11	60180-EDCB13	60180-EDCB20		

Electronic crimper for FTFO and flip-off crimp closures

Product description	13 mm electronic crimper for FTFO	20 mm electronic flip-off crimper		
Ordering information	Cat. no.	Cat. no.		
1/pack	60180-ECR13FO	60180-ECR20FO		

Electronic crimpers and decrimping tools (continued)

Electronic high-power programmable crimp station



Product description	Electronic high-power crimp station (without crimp heads) (black). Generation 2
Ordering information	Cat. no.
1/pack	<u>60180-ECRHB</u>



Electronic high-power programmable crimper kits

Product description	Electronic high-power programmable crimper kit										
Suitable for	11 mm	13 mm	20 mm								
Include	11 mm crimp head 11 mm decrimp head	13 mm crimp head 13 mm decrimp head	20 mm crimp head 20 mm decrimp head								
Ordering information	Cat. no.	Cat. no.	Cat. no.								
1/pack	60180-ECRH11KIT	60180-ECRH13KIT	60180-ECRH20KIT								

Electronic crimpers and decrimping tools (continued)

Accessories for electronic high-power programmable crimper



Product description	Accessory base for electronic crimpers: Height adjustable and solvent resistant (consists of base plate and bar)
Ordering information	Cat. no.
1/pack	<u>ECRH-STAND</u>



Product description	8 mm crimp head	11 mm crimp head	13 mm crimp head	20 mm crimp head	
Ordering information	Cat. no.	Cat. no.	Cat. no.	Cat. no.	
1/pack	ECMJ-8	ECMJ-11	ECMJ-13	ECMJ-20	

Product description	13 mm flip-off crimp head	20 mm flip-off crimp head
Ordering information	Cat. no.	Cat. no.
1/pack	ECMJ-13FO	ECMJ-20FO

Accessories for electronic high-power programmable decrimper

Product description	11 mm decrimp head	13 mm decrimp head	20 mm decrimp head
Ordering information	Cat. no.	Cat. no.	Cat. no.
1/pack	ECDJ-11	ECDJ-13	ECDJ-20

WebSeal Performance level 1 products

Well plates and mats

Performance level 1 for everyday analysis

A full selection of high quality sample well plates for your UHPLC, LC and GC applications

We offer a comprehensive range of Thermo Scientific[™] 96- and 384- well plates for complex and routine analyses in high-throughput screening laboratories.

We offer a broad selection of polypropylene (PP) well plates that meet ANSI and SBS standards with different sealing options and fit most manifolds, autosamplers, and robots.

Handle more samples in less time

· Low volume and high recovery cavity

Solutions for all applications

 Chromatography tested for solvent compatibility and inertness

Ultimate sample security

Low-leachable, high-purity materials and manufacturing processes





Well plates and mats (continued) Performance level 1 for everyday analysis

WebSeal well plates

Plastic, non-coated, non-sterile, chromatography tested

Description

- Thermo Scientific WebSeal well plates are manufactured from a GC/MS tested PP material
- Microplates are chemically and thermally resistant and will tolerate temperatures from –80° C to +121 °C
- SBS and ANSI standard footprint design for broad instrument compatibility
- Microplates are ideal for pharmaceutical applications, sample collection and storage, combinatorial chemistry and HTS applications
- U- and V- bottom wells for optimal sample recovery









Description	Total height	Well format	Total volume (µL)	Working volume range (µL/well)	Pack size	Cat. no.
96 well microplate, round well	14.4	V-shape, 8 mm diameter	450	10-400	20	<u>60180-P100</u>
	14.4	V-shape, 8 mm diameter	450	10-400	120	<u>60180-P130</u>
	14.5	U-shape, 8 mm diameter	500	20-450	10	<u>60180-P102</u>
	14.5	U-shape, 8 mm diameter	500	20-450	120	<u>60180-P132</u>
	26.5	U-shape, 8 mm diameter, mid height plate	1100	50-900	50	<u>60180-P154</u>
	31.6	U-shape, 8 mm diameter, mid height plate	1300	50-1000	5	<u>60180-P103</u>
96 well plates, round well	31.6	U-shape, 8 mm diameter, mid height plate	1300	50-1000	50	<u>60180-P133</u>
	45.3	U-shape, 8 mm diameter, deep-well plate	2000	50-1900	5	<u>60180-P104</u>
	45.3	U-shape, 8 mm diameter, deep-well plate	2000	50-1900	50	<u>60180-P124</u>
	31.9	U-shape, square, mid height plate	1600	50-1300	96	<u>60180-P155</u>
96 deep well plate, square well	43.7	V-shape, square, deep-well plate	2000	50-1900	5	<u>60180-P105</u>
	43.7	V-shape, square, deep-well plate	2000	50-1900	50	<u>60180-P135</u>
	15.5	V-shape, square, micro titer plate	145	4-120	10	<u>60180-P109</u>
384 well microplate	15.5	V-shape, square, micro titer plate	145	4-120	100	<u>60180-P129</u>
	22.0	V-shape, square, mid-height plate	252	5-240	5	<u>60180-P107</u>
	22.0	V-shape, square, mid-height plate	252	5-240	100	<u>60180-P127</u>

Well plates and mats (continued) Performance level 1 for everyday analysis

WebSeal mats and sealing tapes, non-sterile For plates with round and square wells of 8 mm or 384 well plates

Description

- Mats manufactured of EVA (Ethylene-vinyl acetate) or pure silicone with or without PTFE coating
- The footprint permits plates to be securely stacked without robotic arm interference
- Eliminates cross contamination of samples
- Dry heat autoclavable (only silicone mats) with excellent chemical compatibility, withstand low temperature to -80 °C
- Resists coring and tearing
- Superior resealability after multiple injections
- Available pre-slit for easy penetration and reduced vacuum formation
- Sealing tapes minimize evaporation and protect samples from contamination and spilling.
- Adhesive seals effectively seal all microplate formats
- Wide range of adhesive seals for every assay
- Thin, lightweight tapes seal onto the plate with a convenient, handheld applicator (available separately, cat. no. 60180-M950)



60180-M126



60180-M121





60180-M123

60180-M999

Well plates and mats (continued) Performance level 1 for everyday analysis

WebSeal mats and sealing tapes, non-sterile Continued For plates with round and square wells of 8 mm or 384 well plates

Description	Color	Material	Well design	Pre-slit	Pack size	Cat. no.
	Clear	Silicone	96 round well, 8 mm diameter, flat base	Yes	10	<u>60180-M100</u>
WebSeal mats CLR silicone mat, round well	Clear	Silicone	96 round well, 8 mm diameter, flat base	Yes	50	<u>60180-M130</u>
	Clear	Silicone	96 round well, 8 mm diameter, flat base with cross	No	50	<u>60180-M184</u>
WebSeal mats	Clear	EVA	96 round well, 8 mm diameter	No	5	<u>60180-M101</u>
(alcohol resistant), round well	Clear	EVA	96 round well, 8 mm diameter	No	50	60180-M171
WebSeal CLR silicone mat,	Clear	Silicone	96 round well – flat base, 8 mm diameter, large penetration area	No	5	60180-M134
round well	Clear	Silicone	96 round well – flat base, 8 mm diameter, large penetration area	Yes	5	60180-M183
WebSeal mats	Blue	Silicone/ PTFE	96 round well – flat base, 8 mm diameter, large penetration area	No	5	<u>60180-M102</u>
(solvent resistant), round well	Blue	Silicone/ PTFE	96 round well – flat base, 8 mm diameter, large penetration area	Yes	5	<u>60180-M103</u>
WebSeal mats (alcohol resistant),	Clear	EVA	96 square well – flat base	No	5	60180-M177
square well	Clear	EVA	96 square well – flat base	No	50	<u>60180-M178</u>
	Clear	Silicone	96 square well – flat base,	No	5	<u>60180-M121</u>
	Clear	Silicone	8 mm diameter, large penetration area	Yes	5	<u>60180-M123</u>
WebSeal CLR silicone mat,	Clear	Silicone	96 square well – flat base, 8 mm diameter, flat base with cross	No	50	<u>60180-M185</u>
square well	Clear	Silicone	384 square well	No	5	<u>60180-M126</u>
	Clear	Silicone	384 square well	Yes	5	<u>60180-M150</u>
	Clear	Silicone	384 square well, flat base with cross	No	50	<u>60180-M186</u>
Sealing tape, -40 °C – 90 °C	Clear	PE/silicone	_	No	100	<u>60180-M142</u>
Sealing tape, -70 °C – 100 °C	Clear	PES/silicone	_	No	100	<u>60180-M143</u>
Sealing tape, -80 °C – 120 °C	Silver	Aluminum/ silicone	_	No	100	<u>60180-M144</u>
Sealing tape with SRA (synthetic rubber adhesive)	Clear	Polyolefin/ rubber	_	No	100	<u>60180-M145</u>
Re-sealing tape with 3 layer	Clear	PET/silicone/	-	Yes	100	<u>60180-M146</u>
no adhesive at cavity area	Clear	PET	_	Yes	25	<u>60180-M176</u>
Hand held sealing tape applicator	Gold	_	_	_	2	<u>60180-M950</u>
Hand held mat applicator	Black	_	_	_	1	<u>60180-M999</u>
WebSeal cutter for vial removal	Silver	_	_	_	1	<u>60180-M975</u>

WebSeal Performance level 2 products



Well plates and mats

Performance level 2 for high-throughput applications

WebSeal well plates

Plastic, non-coated, non-sterile, certified

Description

- PP microplates are manufactured from ultra low bleed high purity basis resin
- Plates are tested by GC-MS and LC-MS for organic extractables
- Microplates are chemically and thermally resistant and will tolerate temperatures from -80 °C to +121 °C
- SBS and ANSI standard footprint design for broad instrument compatibility
- Microplates are ideal for pharmaceutical applications, sample collection and storage, combinatorial chemistry and HTS applications
- U- and V- bottom wells for optimal sample recovery, total V-plates for low volume applications





60180-P202



60180-P204

60180-P201



WebSeal well plates

Plastic, non-coated, non-sterile, certified

Description	Total height	Well format	Total volume (µL)	Working volume range µL/well	Pack size	Cat. no.
96 well microplate, low volume	15.0	Total V-shape, 5.6 mm diameter	100	5-80	50	<u>60180-P210</u>
	14.7	Flat bottom, 7 mm diameter	380	10-350	100	<u>60180-P205</u>
	14.7	Flat bottom, 7 mm diameter	380	10-350	10	<u>60180-P215</u>
96 well microplate, round well	14.7	U-shape, 7 mm diameter	320	10-300	100	<u>60180-P206</u>
round weir	14.7	U-shape, 7 mm diameter	320	10-270	10	<u>60180-P216</u>
	14.7	V-shape, 7 mm diameter	290	10-250	100	<u>60180-P207</u>
	14.7	V-shape, 7 mm diameter	290	10-250	10	<u>60180-P217</u>
	33	U-shape, 7 mm diameter	1000	50-900	50	<u>60180-P228</u>
96 well mid height plates, round well	41.6	U-shape, 7 mm diameter	1200	50-1100	50	<u>60180-P201</u>
	41.6	U-shape, 7 mm diameter	1200	50-1100	5	<u>60180-P211</u>
96 deep well plate,	44.4	V-shape, 8 mm diameter	2000	50-1900	50	<u>60180-P202</u>
square well	44.4	V-shape, 8 mm diameter	2000	50-1900	5	<u>60180-P212</u>
	14.4	U-shape, square, micro titer plate	58	2-35	60	60180-P203
294 well microrists	14.4	U-shape, square, micro titer plate	58	2-35	10	60180-P213
384 well microplate	30.2	V-shape, square, deep well plate	300	5-240	48	<u>60180-P204</u>
	30.2	V-shape, square, deep well plate	300	5-240	6	<u>60180-P214</u>



WebSeal mats, non-sterile

For certified well plates with 7 mm round well cavities, 8 mm square wells or 384 plates

Description

- Manufactured of pure silicone with or without PTFE coating
- The footprint permits plates to be securely stacked without robotic arm interference
- Eliminates cross contamination of samples
- Dry heat autoclavable with excellent chemical compatibility, withstand low temperature to -80 °C
- Resists coring and tearing
- Superior resealability after multiple injections
- Available pre-slit for easy penetration and reduced vacuum formation



60180-M149



60180-M121



60180-M123



60180-M112





60180-M111

60180-M120

Well plates and mats (continued) Performance level 2 for high-throughput applications

WebSeal mats, non-sterile (continued)

For certified well plates with 7 mm round well cavities, 8 mm square wells or 384 plates

Description	Color	Material	Well design	Pre-slit	Pack size	Cat. no.
WebSeal mat (alcohol resistant), round well	Clear	EVA	96 round well, 7 mm diameter	No	100	<u>60180-M179</u>
	Clear	Silicone	96 round well – flat base, 5.6 mm diameter, cross	No	50	<u>60180-M210</u>
	Clear	Silicone	96 round well – flat base, 7 mm diameter, large penetration area	No	5	<u>60180-M105</u>
WebSeal CLR silicone mat, round well	Clear	Silicone	96 round well – flat base, 7 mm diameter, large penetration area	Yes	5	<u>60180-M116</u>
	Clear	Silicone	96 round well – 7 mm diameter, step, small penetration area	Yes	5	<u>60180-M113</u>
	Clear	Silicone	96 round well – 7 mm diameter, step, small penetration area	No	5	<u>60180-M149</u>
	Clear	Silicone	96 square well – flat base, 8 mm diameter, flat base with cross	No	50	<u>60180-M185</u>
	Clear	Silicone	96 square well – flat base, 8 mm diameter, large penetration area	No	5	<u>60180-M121</u>
WebSeal CLR silicone mat, square well	Clear	Silicone	96 square well – flat base, 8 mm diameter, large penetration area	Yes	5	<u>60180-M123</u>
	Clear	Silicone	384 square well for 384 well plates	No	5	<u>60180-M126</u>
	Clear	Silicone	384 square well for 384 well plates	Yes	5	<u>60180-M150</u>
	Clear	Silicone	384 square well, flat base with cross for 384 microtiter plates	No	50	<u>60180-M186</u>
WebSeal mat (solvent resistant),	Blue	Silicone/ PTFE	96 round well – flat base, step, 7 mm diameter	No	5	<u>60180-M111</u>
round well	Blue	Silicone/ PTFE	96 round well – flat base, step, 7 mm diameter	Yes	5	<u>60180-M112</u>
	Blue	Silicone/ PTFE	96 square well – flat base, 8 mm diameter, large penetration area	No	5	<u>60180-M120</u>
WebSeal mat (solvent resistant),	Blue	Silicone/ PTFE	96 square well – flat base, 8 mm diameter, large penetration area	Yes	5	<u>60180-M122</u>
square well	Blue	Silicone/ PTFE	384 square well for 384 well plates	No	5	<u>60180-M125</u>
	Blue	Silicone/ PTFE	384 square well for 384 well plates	Yes	5	<u>60180-M131</u>
WebSeal mat	Blue	Silicone/ PTFE	96 round well – dome base, 7.2 mm diameter	No	5	<u>60180-M108</u>
	Blue	Silicone/ PTFE	96 round well – dome base, 7.2 mm diameter	Yes	5	<u>60180-M115</u>

WebSeal Performance level 3 products



Well plates and mats

Performance level 3 for high performance analysis

WebSeal Plate+ plates

Glass coated microplates

Description

- High quality PP microplates coated with 200 nm thick layer of silicon dioxide
- Plate+ provides microplates with a chemical resistance similar to glass while retaining the advantages of PP
- Cost-effective alternative to inserted glass vials
- Excellent for applications where plastic microplates are not applicable
- Plate+ is chemically and thermally resistant and will tolerate temperatures from -80° C to +80° C
- Lightweight, precision molded, cost-effective alternative to solid glass plates



Description	Total height	Well format	Total volume (µL)	Working volume (µL)	Pack size	Cat. no.
96 well microplate,	14.4	U-shape, 7.0 mm diameter	320	250	10	<u>60180-P330</u>
	14.4	V-shape, 7.0 mm diameter	350	300	10	<u>60180-P332</u>
round well	14.4	Flat bottom, 7.0 mm diameter	400	350	10	<u>60180-P334</u>
	14.4	V-shape, 7 mm diameter	350	300	100	<u>60180-P333</u>
	26.5	U-shape, 8 mm diameter	1100	50 to 900	10	<u>60180-P350</u>
96 well mid height plate, round well	33	U-shape, 7 mm diameter	1000	50 to 900	10	<u>60180-P343</u>
	40.6	U-shape, 7 mm diameter	1.2 mL	1.0 mL	10	<u>60180-P336</u>
96 deep well plate, square well	43.7	V-shape, 8 mm diameter	2.4 mL	2.0 mL	10	<u>60180-P338</u>
384 well microplate	14.4	Square-rounded, flat, micro titer plate	120	90	10	<u>60180-P340</u>
	14.4	Square-rounded, flat, micro titer plate	120	90	100	<u>60180-P341</u>
	22.0	Square-rounded, U-shape, deep well plate	240	180	6	<u>60180-P342</u>



WebSeal glass inserted plate kits With 96-position mats

Description

- Convenient wellplate kits with pre-assembled glass vials
- Replacement parts for kits available separately
- Unique cutting tool allows removal of individual samples with the seal in place, eliminating cross contamination
- Mats with solid plugs are used for sample storage



60180-K100



60180-K101



60180-K104



60180-K105



60180-K106



60180-K107

WebSeal glass inserted plate kits (continued) With 96-position mats

Kit type	Vial material	Total volume (μL)	Vial dimension (mm)	Profile	Mat material	Total height (mm)	Pack size	Vial cat. no.	Mat cat. no.	Kit cat. no.
96 well small volume microplate with sealing mat	Clear glass	500	6.5 x 31	Taper	Silicone/ PTFE	32.0	5	<u>60180-V100</u>	<u>60180-M151</u>	<u>60180-K100</u>
96 well small volume microplate with	Clear glass	700	6.5 x 41.4	Taper	Silicone/ PTFE	44.0	5	<u>60180-V101</u>	<u>60180-M151</u>	<u>60180-K101</u>
sealing mat and cutting tool	Clear glass	1100	7.45 x 38.5	Round	Silicone/ PTFE	41.5	5	<u>60180-V104</u>	<u>60180-M153</u>	<u>60180-K104</u>
96 deep well plate with sealing mat	Clear glass	1500	7.25 x 60.5	Round	Silicone/ PTFE	64.5	5	<u>60180-V106</u>	<u>60180-M153</u>	<u>60180-K106</u>
96 square well plate with sealing mat	Clear glass	1000	7.6 x 45	Constricted	Silicone/ PTFE	47.3	1	_	<u>60180-M153</u>	<u>60180-K107</u>
96 square well plate with sealing mat	Clear glass	1000	7.6 x 45	Constricted	Silicone/ PTFE Precut	47.3	1	_	<u>60180-M154</u>	<u>60180-K108</u>

WebSeal kit accessories

WebSeal kit accessories

WebSeal 96 well mats Silicone/PTFE

Kit type	Details	Pre-slit	Pack size	Cat. no.
06 well Web Seel met	60180-K100,	No	5	<u>60180-M151</u>
96 well WebSeal mat	60180-K101	Yes	5	<u>60180-M152</u>
96 well WebSeal mat	60180-K104, 60180-K106	No	5	<u>60180-M153</u>
		Yes	5	<u>60180-M154</u>
96 well WebSeal mat,	60180-K107	No	5	<u>60180-M153</u>
welled plugs	60180-K108	Yes	5	<u>60180-M154</u>
WebSeal cutter for vial removal	-	_	1	<u>60180-M975</u>



60180-M151



60180-M154



60180-M975

WebSeal kit accessories (continued)

Plate vials For 96 wells

Kit type	Vial material	Total volume (µL)	Vial dimension (mm)	Profile	Pack size	Cat. no.
	Clear glass	500	6.5 x 31	Taper	500	<u>60180-V100</u>
Micro titer plate vial for 96 wells	Clear glass	700	6.5 x 41.4	Taper	500	<u>60180-V101</u>
	Clear glass	1100	7.45 x 38.5	Round	500	<u>60180-V104</u>
Deep well plate vial for 96 wells	Clear glass	1500	7.25 x 60.5	Round	500	<u>60180-V106</u>



60180-V101

60180-V104

60180-V106

Well plates and racks

Kit type	Plate/ rack material	Total volume (μL)	Profile	Total height (mm)	Pack size	Cat. no.
Plastic 96 round well micro titer plate (60180-K100)	PP	800	V-shape, 7 mm diameter	31.5	5	<u>60180-P400</u>
PP 96 round well micro rack (60180-K101)	PP	1200	U-shape, 7 mm diameter	41.6	5	<u>60180-P211</u>
PP 96 well square well plate (60180-K107/108)	PP	2000	U-shape, square	44.0	1	<u>60180-P403</u>
PP 96 well square well plate (60180-K106)	PP	2000	V-shape, square	44.0	5	<u>60180-P212</u>



60180-P400

Plate vials and accessories

For 96 wells

Kit type	Vial material	Total volume (µL)	Vial dimension (mm)	Profile	Septum	Pack size	Cat. no.
Deep well plate vial for 96 wells	Clear glass	350	6 x 42.5	Taper	—	960	<u>60180-V109</u>
Square well vial for 96 Wells	Clear glass	1000	7.6 x 45.9	Round	_	960	<u>60180-V110</u>
PE cap, red, center hole for 96 Well Plate Inserts	-	_	_	_	Silicone/PTFE, pre-slit, 45°	96	<u>60180-C100</u>
Micro-tube-rack-system, positions (for 60180-K104)	_	_	_	_	_	96	<u>60180-P407</u>



60180-C100

60180-V109

WebSeal kit accessories (continued)

WebSeal clear glass inserted plate kits With individual closures

Description

- 96 position block systems with glass inserts are used when the pure PP block is not inert enough
- Inserts manufactured from clear, Type 1 Class A Glass
- Inserts are sealed individually with a PE Cap Seal and can be easily removed and used externally without risk of losing sample
- The products can be obtained as individual components or as completely assembled, ready-to-use convenience blocks

Kit type	Total volume (µL)	Vial dimension (mm)	Profile	Septum	Pack size	Vial cat. no.	Cap cat. no.	Kit cat. no.
96 deep well Plate	350	6 x 42.5	Taper	Silicone/PTFE, pre-slit, 45°	1	<u>60180-V109</u>	<u>60180-C100</u>	<u>60180-K201</u>
96 square well plate	1000	7.6 x 45.9	Round	Silicone/PTFE, pre-slit, 45°	1	<u>60180-V110</u>	<u>60180-C100</u>	<u>60180-K203</u>



60180-K201

60180-K203

WebSeal kit accessories

(continued)

Barcoded well plates For Thermo Scientific[™] Vanquish[™] HPLC and UHPLC systems

Description

- These well plates provide advanced sample security and sample integrity.
- This secure choice offers a tested portfolio for chromatography applications
- Barcoded well plates have an assured plate fit and a pre-applied orientation barcode in the correct reader position; therefore there is no risk of placing the plate incorrectly
- The secured side orientation in the autosampler alleviates the risk of starting the sequence in the wrong plate orientation
- The instrument controls plate orientation and verifies the plate before implementing the sequence

Description	Total height	Well format	Total volume µL/well	Working volume range µL/well	Pack size	Cat. no.
	14.7	U-shape, 7 mm diameter	320	10-300	100	<u>60180-P206B</u>
96 well microplate,	14.7	U-shape, 7 mm diameter	320	10-300	10	<u>60180-P216B</u>
round well, barcoded	14.7	V-shape, 7 mm diameter	290	10-250	100	<u>60180-P207B</u>
	14.7	V-shape, 7 mm diameter	290	10-250	10	<u>60180-P217B</u>
	31.6	U-shape, 8 mm diameter	1300	50-1000	5	<u>60180-P103B</u>
96 well mid height plate, round well,	31.6	U-shape, 8 mm diameter	1300	50-1000	50	<u>60180-P133B</u>
barcoded	42.0	U-shape, 7 mm diameter	1200	50-900	50	<u>60180-P201B</u>
	42.0	U-shape, 7 mm diameter	1200	50-900	5	<u>60180-P211B</u>
96 deep well plate, square well,	44.0	V-shape, square	2000	50-1900	5	<u>60180-P105B</u>
barcoded	44.0	V-shape, square	2000	50-1900	50	<u>60180-P135B</u>

For mats see previous pages with mats for 7 or 8 mm cavity diameter





P206B/216B

60180-P206B/216B



Learn more at thermofisher.com/surestart

General Laboratory Equipment – Not For Diagnostic Procedures. © 2021-2025 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries unless otherwise specified. Agilent is trademark of Agilent. PAL is a trademark of CTC Analytics AG. Waters, ACQUITY are trademarks of Waters. Shimadzu is a trademark Shimadzu Corporation. PerkinElmer is a trademark of PerkinElmer Inc. TPX is a registered trademark of MITSUI CHEMICALS AMERICA, INC. This information is presented as an example of the capabilities of Thermo Fisher Scientific products. It is not intended to encourage use of these products in any manner that might infringe the intellectual property rights of others. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details. **BR21443-SH-EN 0325**



www.microcolumn.it

